

07/19/00

JUL 15 5 10 PM '00

UTILITY PATENT APPLICATION TRANSMITTAL

Attorney Docket No.

0162/00561

First Named Inventor or Application Identifier

Kunio Kobayashi et al.

Title

SYSTEM AND METHOD FOR QUANTITATIVE
COMPETITION AND RECORDING MEDIUM
HAVING RECORDED THEREON PROGRAM
FOR IMPLEMENTING THEM

Express Mail Label No.

JUL 15 5 10 PM '00

00/19/00

APPLICATION ELEMENTS

ADDRESS TO:

Commissioner for Patents
Box Applications
Washington, D.C. 20231

1. ☒ Filing fee as calculated below.
2. ☒ Specification [Total Pages **106**]

(preferred arrangement set forth below)
- Descriptive title of the invention
- Cross References to Related Applications
- Statement Regarding Fed sponsored R & D
- Reference to Microfiche Appendix
- Background of the Invention
- Brief Summary of the invention
- Brief Description of the Drawings (if filed)
- Detailed Description
- Claim(s)
- Abstract of the Disclosure

3. ☒ Drawing(s) (35 USC 113) [Total Pages **32**]

4. ☐ Oath or Declaration [Total Pages **2**]

- a. ☒ Newly executed (original or copy)

- b. ☐ Copy from a prior application (37 CFR 1.63(d))
(for continuation/divisional with Box 17 completed)

☐ DELETION OF INVENTOR(S)

Signed statement attached deleting inventor(s)
named in the prior application, see 37 CFR
1.63(d)(2) and 1.33(b)

5. ☐ Incorporation By Reference (useable if Box 4b is

*checked) The entire disclosure of the prior application, from
which a copy of the oath or declaration is supplied under Box
4b, is considered as being part of the disclosure of the
accompanying application and is hereby incorporated by
reference therein.

6. ☐ Microfiche Computer Program (Appendix)
7. ☐ Nucleotide and/or Amino Acid Sequence
Submission (if applicable, all necessary)
a. ☐ Computer readable copy
b. ☐ Paper Copy (identical to computer copy)
c. ☐ Statement Verifying identity of above
copies

8. ☒ Assignment papers (cover sheet & document(s))
9. ☐ 37 CFR 3.73(b) Statement ☐ Power of Attorney
10. ☐ English Translation Document (if applicable)
11. ☐ Information Disclosure ☐ Copies of IDS
Statement (IDS)/PTO-1449 Citations
12. ☐ Preliminary Amendment
13. ☒ Return Receipt Postcard (MPEP 503)
(Should be specifically itemized)
14. ☐ Small Entity ☐ Statement filed in prior application,
Statement(s) Status still proper and desired
15. ☒ Certified copy of Priority Document(s)
(if foreign priority is claimed)
14. ☐ Other:

17. If a **CONTINUING APPLICATION**, check appropriate box and supply the requisite information:

☐ Continuation ☐ Divisional ☐ Continuation-in-part (CIP) of prior application No.

18. CORRESPONDENCE ADDRESS

Customer Number or Bar Code Label

or correspondence address below

(Insert Customer No. or Attach bar code
label here)

NAME

Pollock, Vande Sande & Amernick, R.L.L.P.

ADDRESS

Suite 800

1990 M Street, N.W.

CITY

Washington

STATE

DC

ZIP CODE

20036-3425

COUNTRY

U.S.A

TELEPHONE

(202) 331-7111


FAX

(202) 293-6229

Fee Calculation and Transmittal

(Col 1)		(Col 2)		(Col 3)	SMALL ENTITY		NON-SMALL ENTITY	
NO. FILED				NO. EXTRA	RATE	FEE	RATE	FEE
TOTAL	220	minus	20	= 200	x9=	\$	x18=	\$3,960
INDEP	19	minus	3	= 16	x39=	\$	x78=	\$1,248
_ First Presentation, Multiple Dependent Claims					+130=	\$	+260=	\$260
Base Filing Fee						\$345		\$690
Other Fee (specify purpose) <u>Assignment recordation</u>						\$		\$40
TOTAL FILING FEE* (accounting for possible small entity status)						\$	OR TOTAL	\$6,198

- ☒ A check in the amount of \$6,198.00 to cover the filing fee is enclosed
- ☐ No payment is enclosed at this time. Full payment will be made when the executed Declaration is submitted.
- ☒ The Director is hereby authorized to charge and credit Deposit Account No. **22-0185** as described below. A duplicate copy of this sheet is enclosed.
- ☐ Charge the amount of \$__ as filing fee
- ☒ Credit any overpayment.
- ☒ Charge any additional filing fees required under 37 CFR § 1.16
- ☒ Charge any additional filing fees required under 37 CFR § 1.17
- ☒ If filing fee is not enclosed herewith, the filing fee(s) required to Deposit Account No. **22-0185**.

Name (Print/Type)	Morris Liss	Registration No. (Attorney/Agent)	24,510
Signature			Date July 19, 2000

SPECIFICATION

TO ALL WHOM IT MAY CONCERN:

BE IT KNOWN that we KUNIO KOBAYASHI, a subject of Japan and residing at Shinjuku-ku, Tokyo, Japan, HIKARU MORITA a subject of Japan and residing at Shinjuku-ku, Tokyo, Japan and KOUTAROU SUZUKI a subject of Japan and residing at Shinjuku-ku, Tokyo, Japan have invented certain new and useful improvements in

"SYSTEM AND METHOD FOR QUANTITATIVE COMPETITION AND RECORDING MEDIUM HAVING RECORDED THEREON PROGRAM FOR IMPLEMENTING THEM"

and we do hereby declare that the following is a full, clear and exact description of the same; reference being had to the accompanying drawings and the numerals of reference marked thereon, which form a part of this specification.

SYSTEM AND METHOD FOR QUANTITATIVE COMPETITION AND
RECORDING MEDIUM HAVING RECORDED THEREON PROGRAM
FOR IMPLEMENTING THEM

5 BACKGROUND OF THE INVENTION

The present invention relates to a quantitative competition system and method which compare aimed or intended values of participants and publish the highest or lowest value but hide the other values, and a recording medium on which there is recorded a program for implementing the method. More particularly, the invention pertains to a system and method for quantitative comparison of secret values, for example, in electronic lottery, electronic voting, or electronic sealed-bid auction under circumstances where many participants are allowed to access the server online across the Internet.

Fig. 1 is depicts in block form the configuration of a conventional electronic competitive bidding or sealed-bid auction system. A notice of auction is input to bidding devices 10_1 to 10_M , which send their identifiers ID_1 to ID_M and bidding prices PR_1 to PR_M to a bid-opening device 20. In this transfer of each data, if it is desirable to keep the data secret, the bidding price is sent in compressed form, and if it is necessary to identify the data, it is sent together with a digital signature of the bidder. The bid-opening device 20 detects the highest (or lowest) one of the bid values received from the bidding devices 10_1 to 10_M , and outputs the winning bid and the identifier corresponding thereto. This scheme is disclosed, for example, in Japanese Patent Application Laid-Open Gazette No. 118876/90 entitled "Electronic Bidding System." On the other hand, schemes which publish only the winning bid but hide other information involved are disclosed, for example, in Kazuo SAKO, "Auction Protocol Which Hides Bids of Losers," The

Symposium on Cryptography and Information Security, SCIS'99, and in Shingo MIYAZAKI and Kouichi SAKURAI, "A Bulletin-Board Base Digital Auction Scheme with Bidding Down Strategy," The Symposium on Cryptography and Information Security SCIS'99.

5 The sealed-bid auction scheme to which the present invention is applied satisfies the requirements mentioned below.

*Only bidding prices are used to determine the winning bid; that is, the successful bidding device is not determined using other information.

10 * The bid-opening device and a provisional identifier registration device neither cheat nor malfunction.

SUMMARY OF THE INVENTION

15 It is therefore an object of the present invention to provide a quantitative competition system and method which ensure the fairness of a sealed-bid auction, the validity of a successful bid value, the undeniability of bidders, the anonymity of the bidders and the freedom from double bidding.

The fairness of an auction means that it is possible to prevent bidders from obtaining information on other bidding devices prior to bidding in an attempt to make bids with unfair advantage.

20 The validity of a successful bid value means that it is possible to prevent an unfair determination of the winning bid.

The undeniability of bidders means that it is possible to prevent them from denying their bid values at the bid-opening time.

25 The anonymity of bidders means that it is possible to prevent leakage of identification information of every bidding device.

According to the present invention, each bidding device transforms its bidding price to bidding price information through utilization of a one-way

function, and the bid-opening device uses the bidding price information to determine the successful bid without revealing the prices bid by unsuccessful bidders.

5 BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a block diagram showing the general configuration of an electronic competitive bidding system;

Fig. 2 is a flowchart showing the general procedure of an electronic sealed-bid auction;

10 Fig. 3 is a block diagram depicting a bidding device which uses one-way functions to generate a bid index;

Fig. 4 is a block diagram depicting a concrete example of a bidding price transformer using one-way function processors;

15 Fig. 5 is a flowchart showing the procedure for generating the bid index through the use of one-way functions;

Fig. 6 is a block diagram illustrating the functional configuration of a bid-opening device 20 in a first embodiment of the present invention which is designed to determine the highest price bid as the winning bid;

20 Fig. 7 is a flowchart showing the operation of the bid-opening device 20 depicted in Fig. 6;

Fig. 8 is a block diagram illustrating the functional configuration of a bid-opening device in a second embodiment of the present invention;

Fig. 9 is a flowchart showing the operation of the bid-opening device depicted in Fig. 8;

25 Fig. 10 is a block diagram illustrating the functional configuration of a bid-opening device in a third embodiment of the present invention which is designed to determine the highest price bid as the winning bid;

Fig. 11 is a flowchart showing the bid-opening procedure of the bid-opening device depicted in Fig. 10;

Fig. 12 is a block diagram illustrating the functional configuration of a bidding device in a fourth embodiment of the present invention;

5 Fig. 13 is a block diagram illustrating the functional configuration of a bid-opening device in the fourth embodiment;

Fig. 14 is a flowchart showing the bid-opening procedure of the bid-opening device depicted in Fig. 13;

10 Fig. 15 is a block diagram illustrating the functional configuration of a bidding device in a fifth embodiment of the present invention;

Fig. 16 is a flowchart showing the bidding procedure of the bidding device depicted in Fig. 15;

Fig. 17 is a block diagram illustrating the functional configuration of a bid-opening device in a fifth embodiment of the present invention;

15 Fig. 18 is a flowchart showing the bid-opening procedure of the bid-opening device depicted in Fig. 17;

Fig. 19 is a flowchart showing the bid-opening procedure in a modified form of the fifth embodiment;

20 Fig. 20 is a block diagram illustrating the functional configuration of a bidding device in a sixth embodiment of the present invention;

Fig. 21 is a flowchart showing the bidding procedure of the bidding device depicted in Fig. 20;

Fig. 22 is a block diagram illustrating the functional configuration of a bid-opening device in the sixth embodiment;

25 Fig. 23 is a flowchart showing the bid-opening procedure of the bid-opening device depicted in Fig. 22;

Fig. 24 is a flowchart showing a modified form of the bid-opening

procedure depicted in Fig. 23;

Fig. 25 is a block diagram illustrating the functional configuration of a bidding device in a seventh embodiment of the present invention;

Fig. 26 is a flowchart showing the bidding procedure of the bidding device depicted in Fig. 25;

Fig. 27 is a block diagram illustrating the functional configuration of a bid-opening device in the seventh embodiment;

Fig. 28 is a flowchart showing the bid-opening procedure of the bid-opening device depicted in Fig. 27;

Fig. 29 is a flowchart showing a modified form of the bid-opening procedure depicted in Fig. 28;

Fig. 30 is a block diagram illustrating the functional configuration of a bidding device in an eighth embodiment of the present invention;

Fig. 31 is a block diagram illustrating the functional configuration of a bid-opening device in the eighth embodiment;

Fig. 32 is a flowchart showing the bid-opening procedure of the bid-opening device depicted in Fig. 31;

Fig. 33 is a block diagram illustrating an electronic sealed-bid auction system which utilizes a provisional identifier; and

Fig. 34 is a flowchart showing the bidding procedure in the system depicted in Fig. 33.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

First Embodiment

The electronic competitive sealed-bid auction system according to this embodiment comprises, as is the case with Fig. 1, M bidding devices 10_1 to 10_M and a bid-opening device 21, which are accessible to each other. This

system operates as depicted in the flowchart of Fig. 2.

Step S1: Input a notice of auction to each of the bidding devices 10_1 to 10_M . The notice of auction describes bidding conditions such as the name of an object for auction, the highest and/or lowest price bid, the term for bidding and qualifications for bidding, and a method of access to the bid-opening device. The bidding conditions differ with objects for auction.

Step S2: In response to the notice of auction which describes the details of the auction, each bidding device 10_m (where $m = 1, 2, \dots, M$) generates a bidding price, and sends to the bid-opening device 20 the bidding price PR_m and an identifier ID_m by which the bidding device 10_m can be identified.

Step S3: Having received from the respective bidding device 10_1 to 10_M their bidding prices PR_1 to PR_M and identifiers ID_1 to ID_M , the bid-opening device 20 computes the highest (or lowest) one of the bidding prices and determines it to be the winning bid.

Step S4: The bid-opening device 20 outputs the winning bid and the identifier of the bidding device having submitted it.

The above procedure is the same as in the prior art. Since the communication channel between each bidding device 10_m and the bid-opening device 20 is not an anonymous channel, in particular, such a procedure as shown in Fig. 2 allows each bidding device 10_m to learn the bidding prices of the other bidding devices by wiretapping. To avoid this, according to the present invention, each bidding device 10_m uses one-way functions to transform the bidding price to bidding price information, which is sent to the bid-opening device 20.

Referring to Fig. 3, the bidding device 10_m comprises an input part 11, an information storage part 12, a control part 13 and a bidding price

transformer 14. The control part 13 follows a control procedure stored in the information storage part 12 to control operations of the respective parts. The notice of auction, which describes the bidding conditions, is provided in advance via a channel to the bidding device 10_m from the bid-opening device 20 or some other device. In the information storage part 12 there are also stored the identifier ID_m of this bidding device 10_m and an initial value IV_m which is used for bidding. At the time of bidding, the bidding price PR_m provided to the input part 11 is fed via the control part 13 into the bidding price transformer 14. The bidding price transformer 14 uses one-way functions to transform the bidding price PR_m to bidding price information γ_m in integral form. The bidding price information γ_m and the identifier ID_m are sent from a transceiver (not shown) to the bid-opening device 20 via a communication channel. Based on the bidding price information from every bidding device 10_m , the bid-opening device 20 decides the winning bid.

In this embodiment, the bidding price transformer 14 is supplied with the initial value IV_m read out of the information storage part 12 by the control part 13 and the bidding price PR_m , and processes the initial value IV_m by a one-way function by the number of times corresponding to the bidding price PR_m as described below. A one-way function is such a function that, given a variable x , $y(=h(x))$ can easily be computed from x , but when given y , very high computational complexity is needed to compute x such that $y=h(x)$. An output value, obtained by processing the initial value IV_m with the one-way function h by k times like $h(\dots h(h(h(IV_m))))\dots$, will hereinafter be represented by $h^k(IV_m)$.

A concrete example of the bidding price transformer 14 is depicted in Fig. 4 and its procedure in Fig. 5. The bidding price transformer 14 comprises a data storage part 14S, conversion table memory 15, a one-way

function h processor 16 and a one-way function g processor 17. Incidentally, the examples of the bidding device 10_m depicted in Figs. 3 and 4 will also be referred to in describing second and third embodiments of the invention later on, in which case the broken-lined data storage part 14S is provided to store the result D_m of each computation by the one-way function h and the final result C_m of computation. A conversion table, which is stored in the conversion table memory 15, is contained as one bidding condition in the notice of auction, for instance. Each bidding device 10_m reads out the conversion table from a bulletin board 25 of the bid-opening device 20 which will be described later on with reference to Fig. 6. The conversion table is a table on which there are shown appropriately-separated K bidding prices from the lowest to the highest bidding price and a series of corresponding indexes $k = 1, 2, \dots, K$. Each bidding device 10_m selects a desired bidding price from the conversion table and uses the corresponding index k as a bidding price index k_m . In the Fig. 4 example the bidding prices corresponding to the indexes $k = 1, 2, \dots, K$ are arranged to monotonously increase, but by arranging them to monotonously decrease, the lowest bidding price can be made a winning bid.

The one-function h processor is supplied with the initial value IV_m and the price index k_m corresponding to the bidding price PR_m read out of the conversion table memory 15, and repeatedly processes the initial value IV_m with the one-way function h by the number of times corresponding to the price index k_m . As a result, $h^{k_m}(IV_m)$ is obtained. The one-way function g processor 17 further processes the output value $h^{k_m}(IV_m)$ with a one-way function g to compute $\gamma_m = g(h^{k_m}(IV_m))$, and output it as bidding price information.

Step S1: Input the bidding price PR_m and the initial value IV_m .

Step S2: Read out of the conversion table memory 15 the price index k_m corresponding to the bidding price PR_m .

Step S3: In the one-way function h processor 16, set the initial value of a variable t at 0 and the initial value IV_m as γ_m , and repeat steps S4 and S5.

5 Step S4: Determine if t is smaller than k_m .

Step S5: If $t < k_m$, update γ_m with the value of $h(\gamma_m)$ at that time, then increment t by one, and return to step S4.

Step S6: When t becomes no longer smaller than k_m , $\gamma_m = h^{k_m}(IV_m)$, which is processed by the one-way function g processor 17 such that $\gamma_m \leftarrow$
10 $g(\gamma_m)$.

Step S7: Output, as the bidding price information, γ_m obtained in step S6.

BID-Opening Device (Successful Bid: Highest Bidding Price Bid)

Fig. 6 is a block diagram of the bid-opening device 20, which
15 comprises a control unit 21, and a one-way function h processor 22, a one-way function g processor 23, an adder/subtractor 24, a bulletin board 25, a program storage part 27S, an information storage part 35 and an update data storage part 36 which are all connected to the control unit 21. In the program storage part 27S there is stored a bid-opening procedure as a
20 program, and the control unit 21 follows the program to control operations of the respective parts. The one-way function h processor 22 and the one-way function g processor 23 are series-connected. The parts except the bulletin board 25 constitute a winning bid selector 27. The number of bidding devices are M , and the initial value IV_m unique to each bidding device 10 _{m}
25 (where $m = 1, 2, \dots, M$) is prestored by some means in the information storage part 35. In the bulletin board 25 there are also recorded other bidding conditions including a conversion table 25A; furthermore,

verification information and the results of auction to be published are written in the bulletin board 25. The pieces of information are accessible from any external devices as well as from the bidding devices. In this case, however, assume that only the bid-opening device 20 is allowed to write in the bulletin board 25 (This applies to other embodiments).

In Fig. 7 there is depicted the procedure of operation of the bid-opening device 20. In this example the bidding price corresponding to the largest price index k_m is made a successful bid as follows. The index value is decremented one by one from the largest index K corresponding to the upper limit of the bidding price specified in the conversion table; a check is made for the presence of the bidding price information γ_m (where $m = 1, 2, \dots, M$) corresponding to each index k is present; and when the bidding price information γ_m corresponding to the index k is detected for the first time, the detected bidding price information γ_m is determined to be the winning bid, and m (the bidding device number) at that time is computed, with which the bid-opening procedure ends.

Step S0: The bidding device 10_m inputs its bidding price information γ_m and identifier ID_m (where $m = 1, 2, \dots, M$) to the bid-opening device 20.

Step S1: The control unit 21 records the bidding price information γ_m and the identifier ID_m in the bulletin board 25 accessible from arbitrary external devices (the bidding devices 10_1 to 10_M and other devices which are not bidders).

Step S2: To precalculate $D_m^{(1)}, D_m^{(2)}, \dots, D_m^{(K)}$ such that $D_m^{(k)} = h(D_m^{(k-1)})$ in the subsequent steps S3 to S6, the control unit 21 sets the bidding price index $k \leftarrow 1$, then reads out ID_m from the information storage part 35, and substitutes it for $D_m^{(0)}$.

Step S3: The control unit 21 determines whether $k > K$.

Step S4: If not $k > K$, process $D_m^{(k-1)}$ by the one-way function h processor 22 to obtain $D_m^{(k)}$.

Step S5: Store $D_m^{(k)}$ in the update data storage part 36.

Step S6: Increment k by the adder/subtractor 24 such that $k \leftarrow k+1$.

5 Step S7: If $k > K$ in step S3, it means that $D_m^{(1)}=h(D_m^{(0)})=h(IV_m)$, $D_m^{(2)}=h(D_m^{(1)})=h^2(IV_m)$..., $D_m^{(K)}=h^K(IV_m)$ have all been obtained, then set $k \leftarrow K$.

10 Step S8: Read out $D_m^{(K)}=h^K(IV_m)$ from the update data storage part 36 and process it by the one-way function g processor 23 to obtain $D_m^{(k)} \leftarrow g(D_m^{(k)})$.

Step S9: For $m = 1, 2, \dots, M$, the control unit 21 makes a check to see if there exists on the bulletin board 25 the bidding price information γ_m of the same value as $D_m^{(k)}$.

15 Step S10: If there does not exist on the bulletin board 25 the information γ_m of the same value as $D_m^{(k)}$, the control unit 21 inputs k to the adder/subtractor 24 to decrement k by one (i.e., $k \leftarrow k-1$), then returns to step S8, and in steps S8 and S9 it makes a check to see if there exists on the bulletin board 25 the bidding price information γ_m of the same value as $D_m^{(k)}=g(h^k(IV_m))$ for $m = 1, 2, \dots, M$.

20 Step S11: If the information γ_m of the same value as $D_m^{(k)}$ is found on the bulletin board 25 in step S9, then the control unit 21 regards it as the successful price bid and outputs the index k at this time and the bidding device identifier ID_m corresponding to the information γ_m , with which the procedure ends.

25 As described above, a check is made first for a bidding device 10_m having input the bidding price information γ_m equal to $D_m^{(k)}(=g(h^k(IV_m)))$ when the price index k is at the upper limit value K ; if no such a bidding

device is found, then a check is made for a bidding device 10_m having input the bidding price information γ_m equal to $D_m^{(k)}$ when the index k is decremented by one, i.e. $k \leftarrow k-1$; and if no such a bidding device is found, then a check is made for a bidding device 10_m having input the bidding price information γ_m equal to $D_m^{(k)}$ when the index is further decremented by one, i.e. $k \leftarrow k-1$. By making a check, for each decremented value of k , for the bidding device 10_m having input the bidding price information γ_m equal to $D_m^{(k)} (=g(h^k(IV_m)))$, it is possible to find out the price information γ_m corresponding to the largest index k , that is, the highest bidding price PR_m .

Furthermore, each bidding device 10_m sends $h^{k_m+1}(IV_m)$ to the bid-opening device 20 in advance, and the bid-opening device 20 publishes it on the bulletin board 25 and, after determining the successful bidding price, publishes on the bulletin board 25 the highest bidding price index k and the identifier ID_m of the successful bidding device and the verification information $h^k(IV_m)$; in this instance, since k ought to equal k_m , it is possible for an arbitrary device, except the bid-opening device 20, to verify the validity or fairness of the bid-opening process by processing the published verification information $h^k(IV_m)$ with the one-way function h to obtain $h^{k+1}(IV_m)$ and making sure that it matches $h^{k_m+1}(IV_m)$ published prior to the determination of the winning bid. Alternatively, the verification of the bid-opening procedure can be made by publishing the verification information $h^k(IV_m)$ of each bidding device on the bulletin board 25 in advance and making a check to see if the value, obtained by processing $h^{k_m}(IV_m)$ published on the bulletin board 25 with the one-way function h by $(K-k_m)$ times, matches $h^k(IV_m)$.

In the case where the lowest price bid is the winning bid, the bidding prices corresponding to the price indexes k on the conversion table are arranged so that they monotonously increase from the lowest value, as

referred to previously.

In the embodiment described above, all the bidding device 10_1 to 10_M send $h^{k_m+1}(IV_m)$ to the bid-opening device 20 in advance for verification of the results of bid-opening, and the bid-opening device 20 writes it on the bulletin board. It is easy to compute $h^{k+1}(z)$ from $h^k(z)$ in the computation $h^{k+1}(z)=h(h^k(z))$ using the one-way function, but the computation of $h^k(z)$ from $h^{k+1}(z)$ involves too enormous computational complexity to deal with practically. Accordingly, even if the bidding device publishes in advance $h^{k_v}(IV_m)$ computed using an index k_v larger than the bidding price index k_m , there is no possibility of other devices learning the index k_m unless the bid-opening is performed in terms of the index k_m .

The value k_v of the verification information $h^{k_v}(IV_m)$ may be a value $k_v=k_m+A$ which is obtained by adding the bidding price index k_m with a predetermined integer A equal to or greater than 1, or a value $k_v=K+A$ which is obtained by adding the maximum index K with the integer A . In the former case, $h^{k_m}(IV_m)$ is processed A times with the one-way function h and the resulting value is checked for matching the published information $h^{k_v}(IV_m)$. In the latter case, $h^{k_m}(IV_m)$ is processed $K+A-k_m$ times with the one-way function h and the resulting value is checked for matching the published information $h^{k_v}(IV_m)$.

In the embodiment described above, the bidding devices 10_1 to 10_M each convert the bidding price PR to the index k by the conversion table and the initial value IV_m is processed with the one-way function by the number of times corresponding to the index k , but the use of the conversion table is not essential to the present invention. For example, the index k itself may be the bidding price, in which case neither of the bidding devices the bid-opening device requires the conversion table and any one of a series of value k which

monotonously increase one by one within a predetermined range defined by the upper and lower limits given as one of the conditions for auction is chosen as the bidding price PR.

5 SECOND EMBODIMENT

In the first embodiment the bid-opening device 20 must be informed of the initial value IV_m of each bidding device 10_m . In this embodiment, however, the bid-opening device 20 requires the bidding device 10_m to send $D_m = h^k(IV_m)$ corresponding to the price index k , and hence it does not need the initial value IV_m . Since the price index k varies one by one such that $k = 1, 2, \dots, K$, this embodiment utilizes the fact that $h^{k+1}(IV_m) = h(h^k(IV_m))$ holds; the bid-opening device 20 verifies the response $h^k(IV_m)$ from the bidding device in reply to an inquiry k , then computes $g(h^k(IV_m))$, and checks it for matching the bidding price information γ_m (where $m = 1, 2, \dots, M$).

15 A description will be given of the case where the highest bid is the successful bid.

The bidding device 10_m has a configuration in which the data storage part 14S indicated by the broken line in Fig. 4 is added to the bidding price transformer 14. The bidding device 10_m precomputes $D_m = h^k(IV_m)$ by the one-way function h processor 16 for each value $k = 1, 2, \dots, K+1$, and stores it in the data storage part 14S. When inquired about k from the bid-opening device 20, the bidding device 10_m reads out of the data storage part 14S the data $h^k(IV_m)$ corresponding to k and sends it as the response $D_m = h^k(IV_m)$ to the bid-opening device 20. Furthermore, the bidding device 10_m sends to the bid-opening device 20 the data $h^{K+1}(IV_m)$ as the verification information C_m , together with the bidding price information γ_m . As depicted in Fig. 8, the bid-opening device 20 comprises a control unit 21, a one-way function h

processor 22, a one-way function g processor 23, a subtractor 24, a program storage part 27S and a bulletin board 25 accessible from other devices. On the bulletin board 25 there are published a conversion table 25A along with conditions for auction.

5 The bid-opening device 20 operates as depicted in Fig. 9.

The bidding devices 10_m each send $h^{K+1}(IV_m)$ as the verification information C_m in advance to the bid-opening device 20 together with the bidding price information γ_m and the identifier ID_m . The bid-opening device 20 publishes these pieces of data on the bulletin board 25. Let it be assumed
10 here that M bids are submitted, and hence $m = 1, 2, \dots, M$.

Step S1: Write and hence publish on the bulletin board 25 the plural pieces of data sent to the bid-opening device 20, that is, the bidding price information $\gamma_m (= g(h^{km}(IV_m)))$, the verification information C_m and the identifier ID_m .

15 Step S2: Set the initial value of the index k at the upper limit value K by control unit 21.

Step S3: Request each bidding device 10_m to present $D_m = h^k(IV_m)$. The bidding device 10_m reads out of the data storage part 14S the data $h^k(IV_m)$, and sends it to the bid-opening device 20 as D_m .

20 Step S4: Record and hence publish on the bulletin board 25 the data D_m sent from every bidding device 10_m .

Step S5: Generates $h(D_m)$ for each D_m by the one-way function h processor 22.

Step S6: Make a check to see if all the pieces of data $h(D_m)$ match all
25 the pieces of verification information C_m on the bulletin board 25; if no mismatch is found, then determine that they are all correct or valid, and continue the subsequent steps. If a mismatch is found, then sends an error

message to every bidding device 10_m and finish the bid-opening operation.

Step S7: When no mismatch is found in step S6, generate data $g(D_m)$ by the one-way function g processor 23.

Step S8: Make a check to see if each data $g(D_m)$ matches the bidding price information γ_m ; if no match is found, update C_m on the bulletin board 25 with D_m ($C_m \leftarrow D_m$).

Step S10: Set $k \leftarrow k-1$ by the subtractor 24 and return to step S3.

Step S11: If even one of the pieces of information γ_m is found to match with $g(D_m)$ in step S8, decide k at that time as the price index corresponding to the winning bid, and output the index k and the identifier ID_m of the bidding device 10_m having offered the successful bid.

In this instance, the values of losing bids other than the winning one are kept secret from even the bid-opening device 20.

In this embodiment, too, the lowest price bid can be chosen as the winning bid simply by arranging the bidding prices in such a manner as to monotonously decrease relative to a monotonously increasing index k on the conversion table, or by arranging the bidding prices in such a manner as to monotonously increase relative to a monotonously decreasing index k .

20 THIRD EMBODIMENT

In the second embodiment described above, as depicted in Fig. 9, the bid-opening device 20 requires all the bidding devices to present $h^k(IV_m)$ and receive it for each value of the price index k until the first detection of a match between $g(D_m)$ and γ_m in step S3. Accordingly, the sealed-bit auction scheme according to the second embodiment has the defect of a large communication cost. This embodiment requires the bid-opening device 20 to be informed of nothing but the initial value IV_m , publishes only the winning

bid, that is, hides the losing bids, and reduces the communication cost.

The bidding device 10_m is identical in construction as in the second embodiment, and in the constructions of figs. 3 and 4 the data storage part 14S is provided in which there are prestored $D_m^{(1)}, \dots, D_m^{(K)}$ and $C_m = D_m^{(k+1)}$.

5 The bid-opening device 20, shown in Fig. 10, is basically identical in construction with the bid-opening device of Fig. 8, and no description will be repeated, but as will be described below with reference to Fig. 11, the operation of the bid-opening device in this embodiment differs from the operation depicted in Fig. 9.

10 Step S0: The bidding devices 10_1 to 10_M each send in advance the verification information $C_m (= h^{k+1}(IV_m))$ to the bid-opening device 20 together with the bidding price information $\gamma_m (= g(h^{km}(IV_m)))$ and the identifiers ID_m .

15 Step S1: The bid-opening device 20 first publishes the plural pieces of bidding price information γ_m and verification information C_m and the identifiers ID_m on the bulletin board 25.

Step S2: Set the count value k of a counter 24 at the upper limit value K .

20 Step S3: Inquire of all the bidding devices 10_m (where $m = 1, 2, \dots, M$) about whether they have bid the price k .

Step S4: Decide whether there is bidding device having bid with the price index k .

Step S5: If no bidding device have bid the price, decrement k by the subtractor 24 to $k \leftarrow k-1$ and return to step S3.

25 Step S6: When it is found that any one of the bidding devices 10_m has bid with the price index k , request all the bidding devices 10_m to present $h^k(IV_m)$. Each bidding device 10_m reads out of the data storage part 14S the

data $D_m = h^k(IV_m)$ precalculated corresponding to k as depicted in Fig. 4, and sends the read-out data D_m to the bid-opening device 20.

Step S7: Publishes all the responses D_m from the bidding devices 10_m on the bulletin board 25.

5 Step S8: For all the responses D_m , generate $h^{K-k+1}(D_m)$ by the one-way function h processor 22.

Step S9: Check whether each data $h^{K-k+1}(D_m)$ matches the corresponding verification information C_m on the bulletin board 25. If no mismatch is found, decide that the responses D_m are all correct, and proceed
10 to the subsequent steps. If a mismatch is found, send an error message to each bidding device 10_m and finish this bid-opening session for the price index k .

Step S10: When no mismatch is found in step S9, generate $g(D_j)$ by the one-way function g processor 23 for the response D_j (where $1 \leq j \leq M$) from
15 the bidding device 10_j which has identified itself as having bid with the price k .

Step S11: Check whether $g(D_j)$ matches the bidding price information γ_j of the bidding device 10_j on the bulletin board 25. If they match, decide that the bidding device 10_j has bid the price k . If they do not match, send an
20 error message to all the bidding devices and discontinue the session.

As described above, in this embodiment, when no bidding device identifies itself as having bid the price k in reply to the inquiry in step S3, the bidding devices 10_m are not required to send $D_m (= h^k(IV_m))$ to the bid-opening device 20, and hence the communication cost is small as compared
25 with that in the second embodiment accordingly.

As described below, a check is made, if necessary, to see if another bidding device 10_m (different from the device 10_j) has bid a value higher than

k.

Step S12: For t such that $k \leq t \leq K$ and all m 's except j ($1 \leq m \leq M$, $m \neq j$), it is checked whether $g(h^{-k}(h^k(IV_m)))$ matches the bidding price information γ_m on the bulletin board 25 for $t = k, k+1, \dots, K$, and if a match is found, then

5 send an error message to each bidding device concerned and discontinue the bid-opening session.

Step S13: If no match is found, then output the winning bidding price k and the identifier ID_j of the bidding device having offered the winning bid.

With this check or verification, if a bidding device makes a false

10 response to the inquiry about whether it has bid, for example, with k , this dishonest bidding device is detected; that is, this embodiment satisfies the "undeniability" requirement. When this checking does not takes place, the bid-opening device 20 outputs k and ID_j when deciding in step S11 that the bidding device 10_j has bid with k .

15 In this way, this embodiment keeps losing bids, except the winning one, secret from even the bid-opening device 20 and reduces the communication cost.

While in the above the highest price bid is the winning bid, the lowest price bid can be chosen as the successful bid simply by arranging

20 monotonously decreasing (or increasing) values of the bidding price PR on the conversion table in a one-to-one correspondence with monotonously increasing (or decreasing) values of the price index k .

FOURTH EMBODIMENT

25 This embodiment is intended to permit simplification of the processing in the bid-opening device 20 and reduction of the communication cost.

As depicted in Fig. 12, each bidding device 10_m has a construction in which a random generator 18 and an operation part 19 are added to the bidding device shown in Figs. 3 and 4. The random generator 18 generates a random number R_m known only to the bidding device 10_m . The operation part 19 uses the random number R_m and the bidding price PR_m to perform a predetermined operation such as a bit concatenation, exclusive ORing, addition, or multiplication (which operation will hereinafter be denoted by $(+)$), then processes the operation result with the one-way function h , and sends the processed output $h(PR_m(+) R_m)$ to the bid-opening device 20, together with the bidding price information $\gamma_m = g(h^{km}(IV_m))$ and the identifier ID_m .

Fig. 13 illustrates in block form the functional configuration of the bid-opening device 20 in this embodiment, and Fig. 14 is a flowchart for explaining its operation. The bid-opening device 20 has a construction in which one-way function h processors 22' and 22'' and an operation part 26 are added to the device of Fig. 10 and a subtractor 37 is replaced for the counter 24. For simplicity sake, the program storage part 27S is not shown. At the time of bidding every bidding device 10_m (where $m = 1, 2, \dots, M$) sends $h^{K+1}(IV_m)$ to the bid-opening device 20, along with the bidding price information $\gamma_m (= g(h^{km}(IV_m)))$, the identifier ID_m and the random number information $h(PR_m(+) R_m)$.

Step S1: Receive γ_m , $C_m (= h^{K+1}(IV_m))$, $h(PR_m(+) R_m)$ and ID_m from each bidding device 20 and write and hence publish them on the bulletin board 25.

Step S2: Request all the bidding devices 10_m to present their bidding prices PR_m and random numbers R_m .

Step S3: Upon receiving PR_m and R_m from each bidding device 10_m , compute $(PR_m(+) R_m)$ in the operation part 26, then compute $h(PR_m(+) R_m)$ by

the one-way function h processor 22'', and make a check to determine whether the value matches $h(PR_m(+)R_m)$ published on the bulletin board 25.

Step S4: At this point the bid-opening device 20 learns all the bidding prices. The bid-opening device 20 obtains from the conversion table 25A a price index k_{mx} corresponding to the highest value among the bidding prices PR_m . The bidding device (the successful bidding device) which has bid k_{mx} will hereinafter be identified by 10_j . At this point each bidding device cannot learn the bidding prices of the other bidding devices.

Step S5: Send k_{mx} to all the bidding devices 10_m and request them to present $D_m = h^{k_{mx}}(IV_m)$.

Step S6: Each bidding device 10_m reads out $D_m = h^{k_{mx}}(IV_m)$ corresponding to k_{mx} from the data storage part 14S described previously with respect to Fig. 4, and sends the read-out D_m to the bid-opening device 20, which writes on the bulletin board 25 all the pieces of data D_m sent from the bidding devices 10_m .

Step S7: For each D_m , calculates $K+1-k_{mx}$ by a subtractor 37 and generate $h^{K+1-k_{mx}}(D_m)$ by the one-way function h processor 22 from $K+1-k_{mx}$ and D_m .

Step S8: Verify whether $h^{K+1-k_{mx}}(D_m)$ matches the corresponding verification information C_m on the bulletin board 25. If no mismatch is found, decides that all the responses D_m are correct, and proceed to the subsequent steps. If a mismatch is found, sends an error message to each bidding device and discontinue further operation.

Step S9: If no mismatch is found in step S8, generate $g(D_j)$ by the one-way function g processor 23 for D_j presented by the successful bidding device 10_j .

Step S10: Verify whether $g(D_j)$ matches the bidding price information

γ_j in the bidding data of the bidding device 20_j on the bulletin board 25. If they match, decide that the bidding device 10_j has bid with the price index k_{mx} . If they do not match, send an error message to each bidding device and discontinue the current bid-opening session.

- 5 As described below, a check is made, if necessary, to see if another bidding device 10_m (different from the device 10_j) has bid a value higher than k_{mx} .

- Step S11: For $t = k_{mx} + 1, k_{mx} + 2, \dots, K$, compute $h^{t \cdot k_{mx}}(D_m)$ by the one-way function processor 22' and process the computed result by the one-way function g processor 23 to obtain $g(h^{t \cdot k_{mx}}(D_m))$, and verify whether this
10 $g(h^{t \cdot k_{mx}}(D_m))$ matches the bidding price information γ_m on the bulletin board 25 for all m's except j ($1 \leq m \leq M, m \neq j$).

Step S12: If a match is found, then send an error message to each bidding device concerned and discontinue the current bid-opening session.

- 15 If no match found, then output the winning bidding price index k_{mx} and the identifier ID_j of the bidding device 10_j having offered the winning bid.

- For example, in the case where the bidding device 10_m bids with the random number information $h(PR_m(+)R_m)$ and the bidding price information $\gamma_m = g(h^{k_m}(IV_m))$ (where $PR_m' > PR_m$) and presents a price PR_m' higher than the
20 bidding price PR_m and the random number R_m in reply to the request for the presentation of PR_m and R_m in step S2 and the price PR_m' becomes the highest bid value, if the bidding device presents $D_m = h^{k_m}(IV_m)$ in reply to the request for the presentation of $h^{k_m}(IV_m)$ in step S5, it will pass the verifications in steps S7 and S8, incurring the possibility that the price PR_m lower than PR_m'
25 becomes the winning bid. However, this can be prevented because a mismatch is found between $g(D_m) = g(h^{k_m}(IV_m))$ and $\gamma_m = g(h^{k_m}(IV_m))$ in steps S10 and S11.

With the bid-opening device 20, it is possible to specify the winning bid and the corresponding successful bidding device from PR_m , R_m and ID_m with ease, reduce the communication cost and verify that the winning bidding price and the winning device determined from PR_m , R_m and ID_m are true.

5

FIFTH EMBODIMENT

In this embodiment each bidding device sends to the bid-opening device bidding price information containing select information which indicates whether to bid for each of K kinds of biddable prices. As depicted in Fig. 15, the bidding price transformer 14 of the bidding device 10_m comprises a control part 41, a random generator 42, a one-way function h processor 43, a select information generator 45, a (+) operation part 46 and an adder 47.

Let PR_m represent that one of the K kinds of price indexes 1, 2, ..., K which the bidding device 10_m is to actually to bid. The select information denoted by $b_m^{(k)}$ is defined as follows: $b_m^{(k)} = 0$ when the bidding device 10^m does not bid for the price index k such that $1 \leq k \leq K$, and $b_m^{(k)} = 1$ when the bidding device 10_m bids for the price index k . Accordingly, only one piece of information $b_m^{(k)}$ exists for k such that $1 \leq k \leq K$. As mentioned above, the two values of the information $b_m^{(k)}$ may be any values as long as they differ from each other. The information $b_m^{(k)}$ is known only to the bidding device 10_m, which uses it as a random number for each value of the price index k . The bidding device 10_m outputs $\{ID_m, h(1(+)b_m^{(1)}(+)R_m^{(1)}), h(2(+)b_m^{(2)}(+)R_m^{(2)}), \dots, h(K(+)b_m^{(K)}(+)R_m^{(K)})\}$ as bidding price information.

A description will be given, with reference to Fig. 16, of the procedure by which K pieces of bidding price information are prepared.

Step S1: The bidding price PR_m is determined and input.

Step S2: Set the initial value of the price index k to 1.

Step S3: Make a check to see if $k \leq K$.

Step S4: If $k \leq K$, generate the random number $R_m^{(k)}$ by the random generator 42.

5 Step S5: Generate the rice select information $b_m^{(k)}$ by the select information generator 45 in accordance with the bidding price PR_m .

Step S6: The (+) operation part 46 inputs thereinto these pieces of information $R_m^{(k)}$ and $b_m^{(k)}$, and compute $k(+)b_m^{(k)}(+)R_m^{(k)}$. (+) indicates a predetermined appropriate operation, which may be a concatenation, addition, subtraction, multiplication, or the like.

10 Step S7: Process the result of this operation by the one-way function h processor 43 to generate $h(k(+)b_m^{(k)}(+)R_m^{(k)})$.

Step S8: Increment k by one by the adder 47, followed by a return to step S3.

15 Step S9: When k exceeds K and the processing for all values of k ends, the bidding device 10_m sends the identifier ID_m and the bidding price information $\{h(1(+)b_m^{(1)}(+)R_m^{(1)}), \dots, h(K(+)b_m^{(K)}(+)R_m^{(K)})\}$ to the bid-opening device 20.

20 By generating the bidding price information for each price through utilization of the one-way function and sending all the pieces of bidding price information to the bid-opening device 20 as described above, the aimed bidding price can be kept secret.

Fig. 17 illustrates in block form the bid-opening device 20 which performs the bid-opening process based on such bidding price information sent thereto. The bid-opening device 20 comprises a control part 21, a one-way function h processor 22, a subtractor 24, an information storage part 35, a bulletin board 25 and a (+) operation part 51. As is the case with Fig. 8, the

program storage part 27S is also provided but is not shown for the sake of brevity.

Fig. 18 is a flowchart for explaining the operation of this bid-opening device 20.

- 5 Step S0: Receive the bidding price information $\{ID_m, h(1(+))b_m^{(1)}(+))R_m^{(1)}, h(2(+))b_m^{(2)}(+))R_m^{(2)}, \dots, h(K(+))b_m^{(K)}(+))R_m^{(K)}\}$ from the bidding device 10_m (where $m = 1, 2, \dots, M$).

Step S1: Write and hence publish the bidding price information on the bulletin board 25.

- 10 Step S2: Set the price index k to its highest value K .

Step S3: Request each bidding device 10_m to present the random number $R_m^{(k)}$.

- Step S4: The bidding devices 10_m each send the random number $R_m^{(k)}$ to the bid-opening device 20, which writes all the random numbers $R_m^{(k)}$ on
15 the bulletin board 25.

Step S5: Set $b_m^{(k)} = 1$, then input $b_m^{(k)}$ and $R_m^{(k)}$ to the (+) operation part 51 to perform an operation $k(+))1(+))R_m^{(k)}$, and process the result of operation by the one-way function h processor 22 to obtain $h(k(+))1(+))R_m^{(k)}$.

- Step S6: For each m , make a check to see if a match is found between
20 the calculated $h(k(+))1(+))R_m^{(k)}$ and $h(k(+))1(+))R_m^{(k)}$ on the bulletin board 25.

Step S7: If no match is found, decrement k such that $k \leftarrow k-1$, and return to step S3.

- Step S8: If a match is found, determine the k as the successful price index k , then output the price index k and the identifier ID_m of the bidding
25 device 10_m concerned, and discontinue the current bid-opening session.

As described above, according to this embodiment, the bidding price information corresponding to each price index is generated using the one-way

function and all the pieces of bidding price information are sequentially opened in decreasing order from the highest value. This enables non-winning bids to be kept secret.

In the case of choosing the lowest price bid as the successful bid in this embodiment, the bidding device 10_m similarly sends the bidding price information $\{ID_m, h(1(+)b_m^{(1)}(+)R_m^{(1)}), h(2(+)b_m^{(2)}(+)R_m^{(2)}), \dots, h(K(+)b_m^{(K)}(+)R_m^{(K)})\}$ to the bid-opening device 20. The bid-opening device 20 carries out about the same processing as depicted in Fig. 18, but in step S2 the lowest value 1 of the K kinds of biddable price indexes is set to k and in sep S6 the index k is incremented by one such that $k \leftarrow k+1$.

In the case of choosing the highest price bid as the winning bid in this embodiment, since random numbers $R_m^{(t)}$ received from all the bidding devices for t (where $k \leq t \leq K$) are recorded on the bulletin board 25 in step S4, it is possible to detect that $b_m^{(k)} = 0$ for the index larger than the winning price index k, by calculating $h(t(+)b_m^{(t)}(+)R_m^{(t)})$ and comparing it with $h(k(+)b_m^{(k)}(+)R_m^{(k)})$ published on the bulletin board 25. Accordingly, any one can determine if the winning price index k is correct.

In this embodiment it is also possible for each bidding device 10_m to send the set of random numbers $\{R_m^{(k)}\} (k=1, \dots, K)$ to the bid-opening device 20 in advance together with ID_m and $h(k(+)b_m^{(k)}(+)R_m^{(k)})$. In this case, however, the random number $R_m^{(k)}$ is not written on the bulletin board 25 but is stored in the broken-lined information storage part 35. In Fig. 19 there is shown a flowchart for explaining the processing which the bid-opening device 20 performs in such an instance.

25 Sep S0: Receive the bidding price information $\{ID_m, h(1(+)b_m^{(1)}(+)R_m^{(1)}), h(2(+)b_m^{(2)}(+)R_m^{(2)}), \dots, h(K(+)b_m^{(K)}(+)R_m^{(K)})\}$ and random number information $\{R_m^{(1)}, R_m^{(2)}, \dots, R_m^{(K)}\}$ from the bidding devices

10_m (where $m = 1, 2, \dots, M$).

Step S1: Write and hence publish only the bidding price information on the bulletin board 25 and store the random number information in the storage part 35 indicated by the broken line.

5 Step S2: Set the highest possible value K for the price index k .

Step S3: For all m 's, generate $h(k(+))1(+))R_m^{(k)}$ read out of the storage part 35 with $b_m^{(k)}=1$.

Step S4: Verify whether a match is found between $h(k(+))1(+))R_m^{(k)}$ and the pieces of bidding rice information written on the bulletin board 25.

10 Step S5: If no match is found, decrement the price index k by one to $k \leftarrow k-1$ and return to step S3.

Step S6: For the index k for which the mach was found, write and publish all the random numbers $R_m^{(t)}$ ($k \leq t \leq K$) on the bulletin board 25.

15 Step S7: Determine k at this time as the winning price index, then output this index k and the identifier ID_m of the bidding device 10_m having submitted the winning bid, and discontinue the current bid-opening session.

When the lowest bidding price bid is chosen as the successful bid in this case, the index k is set to the smallest possible value, 1 in this example, in 20 step S2 in Fig. 19, then in step S4 the index k is incremented by one, and in step S5 all random numbers $R_m^{(t)}$ which are $1 \leq t \leq k$ are published on the bulletin board 25. The other operations are the same as those described above with reference to Fig. 19.

25 While in the above the select information $b_m^{(k)}$ has been described to be "0" or "1," they may be any values as long as they are two predetermined different integers.

SIXTH EMBODIMENT

In the second embodiment described previously, at the time of bidding each bidding device 10_m sends the bidding price information $\gamma_m = g(h^{km}(IV_m))$ and the verification information $C_m = h^{k-1}(IV_m)$ to the bid-opening device 20, and at the time of bid-opening the bid-opening device 20 requests the bidding device 10_m to send the information $D_m = h^k(IV_m)$, and verifies whether $h(D_m)$ and C_m match for the information D_m received from the bidding device 10_m ; if they match, then the bid-opening device 20 further verifies whether $g(D_m)$ matches the bidding price information γ_m . These verifications need to be made for all of $m = 1, 2, \dots, M$. Accordingly, the amount of data to be processed increases with an increase in the number M of bidding devices used. In addition, the larger the highest value K of the index k , the more the amount of multiple processing by the one-way function h ; hence it is necessary to process an enormous amount of data.

To avoid this, the sixth embodiment utilizes one-way functions to transform the bidding price index k_m to $gm = H_m^{(K)} = h^{K-km}g^{xm}(IV_m)$, which is sent to the bid-opening device 20. x_m is an arbitrary integer equal to or greater than 1 which is determined by the bidding device 10_m . When inquired about whether it has bid with the index k , the bidding device 10_m presents $H_m^{(k-1)} = h^{k-km-1}(g^{xm}(IV_m))$ if k is not its aimed bidding price index k_m , and if it is the aimed value, the bidding device 10_m presents $H_m^{(k-1)} = g^{xm-1}(IV_m)$. The bid-opening device 20 verifies the former with $h(H_m^{(k-1)}) = H_m^{(K)}$ and the latter with $g(H_m^{(k-1)}) = H_m^{(K)}$.

The M bidding devices 10_m indirectly bit the bidding price index values k_m to the bid-opening device 20, which detects the largest one of the index values k_m bit by the bidding devices 10_m . Each bidding device 10_m and the bid-opening device 20 have a conversion table in which K bidding prices

PR_1, PR_2, \dots, PR_K are held in a one-to-one correspondence with K kinds of index values $1, 2, \dots, K$ in increasing order. In this embodiment, as the index value k (where $k = 1, 2, \dots, K$) increases, the value PR_k becomes larger; for example, $PR_1 = 10, PR_2 = 15, PR_3 = 30, \dots, PR_K = 3000$.

5 Fig. 20 illustrates in block form the functional configuration of the bidding device 10_m and Fig. 21 is a flowchart showing its bidding procedure. The bidding device 10_m comprises an input part 11, a control part 13, a bidding price transformer 14, a transceiver 18 and a storage part 12 all of which are interconnected via a common bus 10B. The bidding price
10 transformer 14 is made up of a conversion table 15, a one-way function h processor 16 and a one-way function g processor 17. The control part 13 reads out a bidding procedure program stored in the storage part 12, and follows it to control the respective parts to perform bidding as described below.

15 Step S1: The bidding device 10_m receives via the input part 11 a value PR_m selected from values PR_1, PR_2, \dots, PR_K , an initial value (a positive integer) IV_m and an arbitrary integer x_m equal to or greater than 1.

Step S2: The control part 13 stores IV_m and x_m in the storage part 12.

20 Step S3: The control part 13 refers to the conversion table 15 with PR_m to convert it to an index value k_m and stores it in the storage part 12.

Step S4: The initial value IV_m and the bidding price x_m are read out from the storage part 12, then input to the one-way function g processor 17, wherein the initial value is processed x_m times with the one-way function g to obtain $g^{x_m}(IV_m)$.

25 Step S5: If necessary, $g^{x_m}(IV_m)$ is stored in the storage part 12.

Step S6: $g^{x_m}(IV_m)$, K and k_m are input to the one-way function h processor 16, wherein $g^{x_m}(IV_m)$ is processed $K - k_m$ times with the one-way

function h to obtain

$$H_m^{(K)} = h^{K-k_m}(g^{x_m}(IV_m)).$$

Step S7: $H_m^{(K)}$ is sent as the bidding price information to the bid-opening device 20 via the transceiver 18.

- 5 In this way, the bidding device 10_m sends the aimed bidding price index value k_m to the bid-opening device 20.

Step S8: Upon beginning the bid-opening procedure by the bid-opening device 20 after the bidding, each bidding device 10_m receives an inquiry with the price index k from the bid-opening device 20 by the transceiver 18 as depicted in Fig. 21.

Step S9: A check is made to see if the inquiry index value k is equal to the bidding price index k_m stored in the storage part 12.

- Step S10: If not equal, $g^{x_m}(IV_m)$ is read out of the information storage part 12 and is input to the one-way function h processor 16 together with k_m and k , wherein $g^{x_m}(IV_m)$ is processed $k-k_m-1$ times with the one-way function h to obtain response information $H_m^{(k-1)}$ by the following equation:

$$H_m^{(k-1)} = h^{k-k_m-1}(g^{x_m}(IV_m))$$

- Step S11: The bidding device 10_m sends the response information $H_m^{(k-1)}$ to the bid-opening device 20 via the transceiver 18 and waits for the next inquiry about k .

Step S12: If the inquiry about k corresponds to its aimed value, that is, if the index k is equal to k_m in the storage part 12, the bidding device 10_m inputs the initial value IV_m and x_{m-1} to the one-way function g processor 17, wherein the initial value IV_m is processed x_m-1 times to obtain response information $H_m^{(k-1)} = g^{x_m-1}(IV_m)$.

Step S13: The bidding device 10_m sends the response information $H_m^{(k-1)}$ to the bid-opening device 20.

The functional configuration of the bid-opening device 20 is depicted in Fig. 22 and its bid-opening procedure in Fig. 23. The bid-opening device 20 comprises a control part 21, a program storage part 27S, a one-way function h processor 22, a one-way function g processor 23, a counter 24, a bulletin board 25, a conversion table 25A, a transceiver 28, and an information storage part 25, all of which are interconnected via a common bus 20B.

Step S1: Upon receiving the bidding information $\gamma_m = H_m^{(K)}$ from each bidding device 10_m by the transceiver 28, the control part 21 writes the bidding information $H_m^{(K)}$ on the bulletin board 25 to publish it.

Step S2: Set K as the initial value of k in the counter 24.

Step S3: Send the index value k on the counter 24 to each bidding device 10_m, and send thereto an inquiry about bidding via the transceiver 28.

Step S4: Receive the response information $H_m^{(k-1)}$ by the transceiver 28 from all the bidding devices 10_m.

Step S5: Input $H_m^{(k-1)}$ to the one-way function h processor 22 to process it with the one-way function h to obtain $h(H_m^{(k-1)})$.

Step S6: Check whether the result of operation $h(H_m^{(k-1)})$ is equal to the bidding information A_m for m in the storage part 35.

Step S7: If $h(H_m^{(k-1)}) = H_m^{(K)}$, store the received information $H_m^{(k-1)}$ as updated bidding information $H_m^{(K)}$ in the storage part 35 to update $H_m^{(K)}$.

Step S8: Decrement the count value k of the counter 24 by one, then return to step S3, and inquire of each bidding device 10_m about whether it has made a registration for the value k.

Step S9: When it is found in step S6 that the response information $H_m^{(k-1)}$ from the bidding device 10_m is $g^{xm-1}(IV_m)$ which is equal to the aimed index value, $h(H_m^{(k-1)})$ does not become equal to $H_m^{(K)} = h^{ek+1-km-1}(g^{xm}(IV_m)) =$

$g^{xm}(IV_m)$ in step S9. Then, input $H_m^{(k-1)}$ to the one-way function g processor 23 to process $H_m^{(k-1)}$ with the one-way function g to obtain $g(H_m^{(k-1)})$.

Step S10: Make a check to see if $g(H_m^{(k-1)})$ is equal to $H_m^{(K)}$ corresponding to m stored in the storage part 35.

- 5 Step S11: When the bidding device 10_m has performed correct processing, $h^{km+1-km-1}(g^{xm}(IV_m)) = g^{xm}(IV_m) = H_m^{(K)}$ by the process of step S7 at the time of previous inquiry for $k = k_{m+1}$; hence, $g(H_m^{(k-1)}) = H_m^{(K)}$ holds. In the inquiry processing for the index k which is decremented one by one, the index k for which $g(H_m^{(k-1)}) = H_m^{(K)}$ holds for the first time is the maximum
- 10 value among the bidding price indexes of all the bidding devices, and this index k is converted to the value PR_k by referring to the conversion table 25A.

Step S12: Output the value PR_k as the highest one of the bid values, and if necessary, output the number m of the winning bidding device 10_m as well.

- 15 In the bidding procedure of Fig. 21, if $k = k_m$ in step S9 when inquired about whether it has bid k , the bidding device 10_m may send to the bid-opening device 29 in step S13 not only the response information $H_m^{(k-1)}$ but also information indicating $k = k_m$ (which information will hereinafter be referred to as identity information). In this instance, upon receiving the
- 20 response information $H_m^{(k-1)}$ in step S4 in Fig. 23, the bid-opening device 20 makes a check for the identity information; if not having received it, the device 20 performs the operation $h(H_m^{(k-1)})$ and if having received the information, $g(H_m^{(k-1)})$. Incidentally, in the event that $g(H_m^{(k-1)}) \neq H_m^{(K)}$ in step S10 in Fig. 23, the bid-opening device 20 may discontinue the current
- 25 bid-opening session for the reasons of dishonesty by the bidding device concerned and request all the bidding devices 10_m to rebid; alternatively, the bid-opening device 20 may abandon inquiring that bidding device but may

continue inquiring the other bidding device.

- In the case where the bidding prices PR_k are arranged on each of the conversion tables 15 and 25A in such a decreasing order as 3000, 2950, 2900, ..., 100 in correspondence with the K index values 1, 2, ..., K , the price PR_k corresponding to the index value k for which $g(H_m^{(k-1)}) = H_m^{(K)}$ holds for the first time in the inquiry about bidding k represents the lowest one of the aimed bidding prices of all the bidding devices 10_m . The maximum value of the index may also be obtained without using the conversion table 15. In this instance, the bidding device 10_m sends the index value k_m , and after step S10 in Fig. 23 the bid-opening device 20 outputs the index value k as the highest value and, if necessary, together with the number m (or ID_m) of the bidding device 10_m having sent the index value k_m .

- In the bid-opening procedure depicted in Fig. 23, the bid-opening device 20 inquires every bidding device 10_m for each value of the index $k = K, K-1, K-2, \dots$, and receives $H_m^{(k-1)}$, and then processes it using the one-say function h in step S5; hence this procedure requires high communication cost and computational complexity. In Fig. 24 there is depicted a modified form of the above-mentioned bid-opening procedure whose communication cost and computational complexity are reduced using the scheme described previously with reference to Fig. 11. No description will be given of the bidding procedure since it is exactly the same as in the Fig. 11 embodiment.

Step S0: Receive bidding price information $H_m^{(K)} = h^{K-k_m}(g^{x_m}(IV_m))$ and the identifier ID_m from each bidding device.

Step S1: Publish the received $H_m^{(K)}$ and ID_m on the bulletin board 25.

- Step S2: Set the initial value of the index k at K .

Step S3: Inquire of all the bidding devices 10_m about whether they bid for the index k .

Step S4: Check the responses for YES (which means that the bidding device concerned has bid for the index k).

Step S5: If no YES is found, decrement k by one and returns to step S3 to repeat the same processing.

- 5 Step S6: If YES is found, request all the bidding devices 10_m to send their bidding price information $H_m^{(k-1)}$. The response of the bidding device to this request is the same as described previously in connection with Fig. 21.

Step S7: Publish the received information $H_m^{(k-1)}$ on the bulletin board 25.

- 10 Step S8: For the response $H_m^{(k-1)}$ of an m (representing the bidding device 10_m) having bid for the index k , compute

$$H_m = h^{K-k}(g(H_m^{(k-1)}))$$

and for the responses $H_m^{(k-1)}$ from the other m 's (the other bidding devices), compute

- 15 $H_m = h^{K+1-k}(H_m^{(k-1)}).$

Step S9: Check whether $H_m = H_m^{(k)}$ holds for all the m 's, and if a mismatch is detected for even one of them, send an error message to all the bidding devices and discontinue the current bid-opening session.

- 20 Step S10: If a match is detected for every one of them, determine that the bidding device 10_m of the number m having responded YES is the winning bidder, and output the index k at that time and its identifier ID_m for publication

The bidding device 10_m and the bid-opening device 20 can each be implemented by a computer.

25

SEVENTH EMBODIMENT

In the fifth embodiment described previously, each bidding device 10_m

generates the select information $b_m^{(k)}$ indicating whether to bid for every price index $k = 1, 2, \dots, K$, and these pieces of select information are contained in K pieces of information $h(k(+))b_b^{(k)}(+))R_m^{(k)}$, where $k = 1, 2, \dots, K$. In this embodiment, however, the plural pieces of select information are contained in a single piece of bidding price information through multiple processing with the one-way function h .

Fig. 25 illustrates in block form the functional configuration of each bidding device 10_m. Assume that K bidding prices PR and the k price indexes $k = 1, 2, \dots, K$, which have a one-to-one correspondence with each other, are both arranged in monotone increasing order in the same direction. The bidding select information for each index k will be identified as $b^{(k)}$. In this embodiment a select information generating part 54 does not generate the select information $b_m^{(k)}$ for all the indexes $k = 1, 2, \dots, K$ but instead generates the select information $b_m^{(k)}$ only for indexes higher than the bidding price index k_m . $H_m^{(k)} = h(H_m^{(k-1)} || b_m^{(k)})$ is calculated, with $H_m^{(k_m-1)} = IV_m$ as its initial value, for each value of the price index $k (=k_m, k_m+1, \dots, K)$ by a one-way function h processor 16, a concatenator 55 and a buffer 56, and the calculation result $H_m^{(k)}$ for each value of k is stored in a data storage part 14S. The final calculation result $H_m^{(K)}$ will hereinafter be called bidding price information. In this embodiment, a signature $Sig_m(H_m^{(K)})$ is generated by a signature generator 14S for the bidding price information 57.

Fig. 26 is a flowchart showing the bidding procedure of the bidding device 10_m depicted in Fig. 25.

In this embodiment, letting k_m be the index that the bidding device 10_m bids, a select information generating part 54 generates $K-k_m+1$ pieces of select information $b_m^{(k_m)}, b_m^{(k_m+1)}, \dots, b_b^{(K)}$ corresponding to the indexes larger than the bidding price index k_m (step S1). Then, $H_m^{(k_m-1)}, H_m^{(k_m)}, H_m^{(k_m+1)}, \dots,$

$H_m^{(K)}$ are successively generated by the following equations

$$H_m^{(km-1)} = IV_m$$

$$H_m^{(km)} = h(H_m^{(km-1)} || b_m^{(km)})$$

$$H_m^{(km+1)} = h(H_m^{(km)} || b_m^{(km+1)})$$

:

$$H_m^{(t)} = h(H_m^{(t-1)} || b_m^{(t)})$$

:

$$H_m^{(K)} = h(H_m^{(K-1)} || b_m^{(K)})$$

and they are stored in the data storage part 14S (step S2). Further, a

signature $\sigma_m = \text{Sig}_m(H_m^{(K)})$ of the bidding device 10_m corresponding to the bidding price information $H_m^{(K)}$ is generated by the signature generator 14S

(step S3). The bidding device 10_m sends $H_m^{(K)}$, σ_m and ID_m as bidding information to the bid-opening device 20 (step S4). After this, the bid-opening procedure is started, and upon receiving an inquiry for each value of

the index k, the bidding device reads out $\{H_m^{(k-1)}, b_m^{(k)}\}$ from the data storage part 14S, and sends it to the bid-opening device (step S5).

The bid-opening device 2- comprises, as depicted in Fig. 27, a control part 21, a one-way function h processor 22, a counter 24, a bulletin board 25,

an information storage part 35, comparators 58 and 59 and a signature verifier

33. The pieces of bidding information $H_m^{(K)}$, σ_m and ID_m are written on the bulletin board 25. Then, the received information $H_m^{(k-1)}$ is processed by the

one-way function h processor 22 to obtain $H_m^{(k)} = h(H_m^{(k-1)})$, which is compared by the comparator 58 with $H_m^{(k)}$ read out of the bulletin board 25 to

thereby verify whether they match. Further, it is checked by the comparator

59 whether the received select information $b_m^{(k)}$ is 1, and if it is 1, then the

bidding device 10_m corresponding to m at that time is determined as the winning bidder.

Fig. 28 is flowchart showing the bid-opening procedure of the bid-opening device 20.

The bid-opening device 20 verifies respective signatures σ_m (where $m = 1, 2, \dots, M$) and writes and publish the received pieces of information $H_m^{(K)}$, σ_m and ID_m on the bulletin board 25.

- 5 The bid-opening device 20 sends k to the bidding device in the order $[k = K, K-1, K-2, \dots]$ and asks for information $\{H_m^{(k-1)}, b_m^{(k)}\}$ corresponding to each index k . The information $\{H_m^{(k-1)}, b_m^{(k)}\}$ received from each bidding device 10_m is published on the bulletin board 25, then it is checked whether
- 10 $H_m^{(k)} = h(H_m^{(k-1)}, b_m^{(k)})$ holds for the information $H_m^{(k)}$ received previously, and if it holds, it is checked whether the select information $b_m^{(k)}$ is 1. When $b_m^{(k)}$ is 0 for all of $m = 1, 2, \dots, M$, the bid-opening device 20 decrements k to $k \leftarrow k-1$, then sends again k to the bidding device and asks for the information $\{H_m^{(k-1)}, b_m^{(k)}\}$, thereafter performing the same operation as described above.
- 15 If the select information $b_m^{(k)}$ is 1 for any one of $m = 1, 2, \dots, M$, then the bidding device 10_m corresponding to that m is determined as the winning bidder. The bid-opening device 20 publishes the successful bidding price index k_m and the identifier ID_m of the wining bidding device 10_m on the bulletin board 25.

- 20 According to this embodiment, since each bidding device does not perform the multiple processing with the one-way function for indexes smaller than the bidding price index k_m , the computational complexity is low accordingly.

- 25 The bid-opening device performs the bid-opening procedure as described below.

Step S0: Receive the pieces of bidding information $H_m^{(K)}$, σ_m and ID_m from each bidding device, then verifies respective signature σ_m (where $m = 1,$

2, ..., M), and writes and publishes the pieces of information $H_m^{(k)}$, σ_m and ID_m on the bulletin board 25.

Step S1: Set the initial value of the index k to K .

Step S2: Send k to each bidding device 10_m and ask for $\{H_m^{(k-1)}, b_m^{(k)}\}$.

5 Step S3: Write and publish on the bulletin board 25 the information $\{H_m^{(k-1)}, b_m^{(k)}\}$ received from each bidding device 10_m .

Step S4: Process the received information $\{H_m^{(k-1)}, b_m^{(k)}\}$ by the one-way function h processor 22, thereby generating $H = h(H_m^{(k-1)} || b_m^{(k)})$.

10 Step S5: Verify by the comparator 58 whether H generated in step S4 matches the previously received $H_m^{(k)}$. If a mismatch is detected, then send an error message to the bidding device and discontinue the current bid-opening session.

Step S6: If no mismatch is found in step S5, then decides that the response from every bidding device is valid, and make a check by the
15 comparator 59 to see if the received select information $b_m^{(k)}$ is 1.

Step S7: When the select information $b_m^{(k)}$ from all bidding devices 10_m is 0, update k with $k-1$ and return to step S2.

Step S8: When any one of M pieces of select information $b_m^{(k)}$ is 1 in
20 step S6, determine that the bidding device 10_m corresponding to m , which provides that information $b_m^{(k)}$, is the winning bidder, and write and publish its identifier ID_m and the index k_k of the winning bid on the bulletin board 25, and end the bid-opening procedure.

In this embodiment the prices bid by the unsuccessful bidders are each
25 kept secret from the other participants. The lowest price bid can be made a successful bid by using a conversion table wherein the price PR monotonously increases in the direction opposite to that in which the index k monotonously increases.

Incidentally, it is also possible to set $H_m^{(0)} = IV_m$, $H_m^{(1)} = h(H_m^{(0)} || b_m^{(1)})$,
 ..., $H_m^{(K)} = h(H_m^{(K-1)} || b_m^{(K)})$, where $b_m^{(1)} = b_m^{(2)} = \dots = b_m^{(km-1)} = 0$.

The communication cost and computational complexity involved in the bid-opening procedure of Fig. 27 can also be reduced, as depicted in Fig. 27', by the application of the scheme described previously with reference to Fig. 11. The bidding procedure is exactly the same as in Fig. 25, and hence it will not be described.

Step S0: Receive the bidding price information $H_m^{(K)} = h(\dots h(H_m^{(km-1)} || b_m^{(km)})) || b_m^{(km+1)}) \dots || b_m^{(K)}$ and the identifier ID_m from each bidding device.

Step S1: Publish the received $H_m^{(K)}$ and ID_m .

Sep S2: Set the initial value of the index k at K .

Step S3: Inquire of all the bidding devices 10_m about whether they bid for the index k .

Step S4: Check the responses for YES (which means that the bidding device concerned has bid for the index k).

Step S5: If no YES is found, decrement k by one and returns to step S3 to repeat the same processing.

Step S6: If YES is found, request all the bidding devices 10_m to send their bidding price information $H_m^{(k-1)} = h(\dots h(H_m^{(km-1)} || b_m^{(km)})) || b_m^{(km+1)}) \dots ||$

$b_m^{(K)}$). The response of the bidding device to this request is the same as described previously in connection with Fig. 21. For the bidding device having bid for the current index k , $k = k_m$; therefore, $H_m^{(k-1)} = H_m^{(km-1)} = IV_m$.

Step S7: Publish the received information $H_m^{(k-1)}$ on the bulletin board

25.

Step S8: For the response $H_m^{(k-1)}$ of an m (representing the bidding device 10_m) having bid for the index k , compute

$$H_m = h(\dots h(h(H_m^{(k-1)} || 1) || 0) \dots 0)$$

and for the responses $H_m^{(k-1)}$ from the other m's (the other bidding devices), compute

$$H_m = h(\dots h(h(H_m^{(k-1)}) \parallel 0) \parallel 0) \dots \parallel 0).$$

- Step S9: Check whether $H_m = H_m^{(k)}$ holds for all the m's, and if a mismatch is detected for even one of them, send an error message to all the bidding devices and discontinue the current bid-opening session.

- Step S10: If a match is detected for every one of them, determine that the bidding device 10_m of the number m having responded YES is the winning bidder, and output the index k at that time and its identifier ID_m for publication.

EIGHTH EMBODIMENT

- In each of the embodiments described above, the bidding prices for the bidding price indexes $k = 1, 2, \dots, K$ in the conversion table are discrete values such as 1000, 2000, 3000, ..., 10000, and each bidding device bids any one of the K prices but cannot bid a value intermediate between such discrete prices unless K prices are set in "1" increments. This embodiment is intended to permit bidding an arbitrary price intermediate between the discrete values. In this embodiment, an arbitrary bidding price PR within the range defined by the highest and lowest bidding prices is expressed by the following equation.

$$PR = F(k) + Q$$

$$\text{where: } 0 \leq Q < F(k+1) - F(k)$$

- F(k) represents the price corresponding to the index k specified on the conversion table, and Q will hereinafter be referred to as a fraction.

This embodiment is one that the bidding price PR defined above is applied to the first embodiment described previously. Bidding price

information $g(h^k(IV_m))$ and Q_m are sent to the bid-opening device 20. Further, $h^{k+1}(IV_m)$ is sent as verification information to the bid-opening device 20 together with the bidding price information. These pieces of information are published on the bulletin board as is the case with the first embodiment.

Fig. 30 is a block diagram illustrating the configuration of each bidding device 10_m, which is identical with the bidding device of the first embodiment except that the bidding price transformer 14 is provided with a fraction calculating part 14a. The fraction calculating part 14a calculates, for a desired bidding price PR_m , $Q_m = PR_m - F(k_m)$ from the index k_m read out of the conversion table 15. As is the case with the first embodiment, the one-way function h processor 16 and the one-way function g processor 17 are used to compute $\gamma_m = g(h^{k_m}(IV_m))$ from the index k_m which satisfies $F(k_m+1) > PR_m \geq F(k_m)$ and the initial value IV_m . In this embodiment, γ_m , Q_m and ID_m are sent as bidding information to the bid-opening device 20.

The bid-opening device 20 has, as depicted in Fig. 31, a sequencer 61 added to the bid-opening device 20 in Fig. 6 embodiment. The pieces of bidding information γ_m , Q_m and ID_m are written and published on the bulletin board 25. The sequencer 61 reads out Q_1, Q_2, \dots, Q_M from the bulletin board 25, then sequences them in descending order, and sequences $m = 1, 2, \dots, M$ corresponding to the sequenced Q_m , thereafter outputting them in the sequential order. The control part 21 checks, for each index k , whether ID_m and γ_m match each other in the sequence of m defined by the sequencer 61. The bidding device 10_m, which corresponds to m for which the match was detected for the first time, is determined as the winning bidder.

Fig. 32 is a flowchart depicting the bid-opening procedure of the bid-opening device 20 shown in Fig. 31, which steps S0 to S7 are identical with steps S0 to S7 in Fig. 7 but differ in step 8 and the subsequent steps.

Roughly speaking, steps S8 and S9 are new steps added between steps S7 and S8 in Fig. 7. Step S8 and the subsequent steps will be described below.

In step S8 the bid-opening device 20 makes a check to determine whether the matching in steps S6 to S11 has been completed for all fractions Q_m for the current value of k . If not completed, the procedure goes to step S9. In step S9, the bid-opening device 20 selects the largest one of the remaining fractions Q_m to determine the corresponding m . In step S10, the device 20 reads out of the data storage part 36 updated data $D_m^{(k)} = h^k(IV_m)$ corresponding to that m , and processes the read-out data by the one-way function g processor 23, thereby updating it such that $D_m^{(k)} \leftarrow g(D_m^{(k)})$. In step S11, the control device 21 makes a check to see if the updated data $D_m^{(k)}$ corresponding to m matches the bidding price information γ_m corresponding to m on the bulletin board 25, and if not, then the procedure returns to step S8.

When it is decided in step S8 that the matching for all the fractions Q_m for the current k has been completed, the bid-opening device 20 decrements k by one in step S12, and returns to step S8, repeating the same procedure as mentioned above. When it is decided in step S11 that the updated data $D_m^{(k)}$ and the bidding price information γ_m match, the bid-opening device 20 determines in step S13 that the index k at that time is the successful index, and outputs the identifier ID_m corresponding to that information γ_m and the successful bidding price $F(k) + Q_m$ (or merely the index k).

Since $D_m^{(k)}$ and γ_m are matched for the current value of the index k in the descending order of the fractions Q_m as described above, the highest bidding price can be determined at the first detection of matching between $D_m^{(k)}$ and γ_m . The value m selected in step S9 is determined by the sequencer 61 which sequences in descending order the fractions Q_1, Q_2, \dots, Q_M read out of the bulletin board 25, and sequences m correspondingly, as explained

before.

In the case where the lowest bidding price bid is a successful bid, the bidding prices are arranged in monotonous increasing order in the direction opposite to that in which the values of the index k are arranged in monotonous decreasing order, and the sequencer 61 sequences the fractions Q_1, Q_2, \dots, Q_M in ascending order, and sequences m correspondingly. In step S9 the smallest one of the unprocessed fractions Q_m is chosen, and the corresponding m is determined. The sequencer 61 determines the order of m .

The technique that uses many fractions Q_m as described above can be applied not only to the first embodiment but also to the other embodiments explained heretofore.

Electronic Competitive Auction System With Provisional Identifier Device

In the embodiments described above, since the bidding device identifier ID_m is contained in the bidding information and sent to the bid-opening device 20, it can be said that these embodiments employ what is called a sealed-bit auction system. Fig. 33 illustrates in block form an electronic competitive auction system which uses a provisional identifier registration device to implement a secret-bit auction.

Each bidding device 10_m is adapted to communicate with a provisional identifier registration device 70. Referring to Fig. 34, the operation of this electronic competitive auction system will be described below.

Step S0: Notice of auction is input to each bidding device 10_m .

Step S1: Upon receiving the notice of auction, the bidding device 10_m outputs the identifier ID_m to the provisional identifier registration device 70.

Step S2: For the identifier ID_m provided thereto, the provisional identifier registration device 70 issues a provisional identifier AID_m , then

stores ID_m and AID_m in pair form on a recording medium 71, and sends the provisional identifier AID_m to the bidding device 10.

Step S3: The bidding device 10_m: generates the bidding price PR_m ;

Step S4: Transforms the bidding price PR_m to the bidding price information γ_m ; and

Step S5: Sends the bidding price information γ_m and the provisional identifier AID_m to the bid-opening device 20.

Step S6: The bid-opening device 20: calculates a successful bid from the bidding price indexes received from all the bidding devices; and

Step S7: Outputs the successful bid and the provisional identifier of the bidding device having offered the successful bid.

Thus, it is possible to keep the auction participants secret. Incidentally, when inquiring the provisional identifier registration device 70, the bid-opening device 20 can learn the identifier ID_m corresponding to the successful bid from the provisional identifier AID_m . This method can be applied to all of the embodiments explained hereinbefore.

The bidding device 10_m and the bid-opening device 20 can be implemented by interpreting and executing programs with a computer.

20 EFFECT OF THE INVENTION

As described above, according to the present invention, since the bidding price is transformed to a bidding price information through utilization of a one-way function and is then sent to the bid-opening device, it is possible to keep the bidding price of each bidding device secret from the other bidding devices prior to bidding, ensuring fairness of auction.

By publishing $h^{K+1}(IV_m)$ and $h^{kmx}(IV_m)$ corresponding to a winning bidding price on the bulletin board, it is possible for all bidding devices to

verify whether the winning bidding price was correctly bid without being altered.

Furthermore, the present invention permits determination of the winning bid while hiding the other bidding prices.

5 According to the second embodiment, the bids of losing bidders, except the winning bid, are kept secret even from the bid-opening device.

According to the third embodiment, the bids of losing bidders, except the winning bid, are kept secret even from the bid-opening device, and in addition, the amount of data for communication with the bidding device can
10 be reduced.

According to the fourth embodiment, there is no fear of the bidding price of each bidding device being revealed to the other devices, and at the bid-opening time the successful bid can easily be specified directly from the bidding price; furthermore, the validity of the winning bid can be verified.

15 According to the fifth embodiment, bidding price information including each bidding price index is generated using a one-way function, and the bidding price information for all bidding price indexes is sent to the bid-opening device; hence, the aimed bidding price can be kept secret.

According to the sixth embodiment, either $h(H_m^{(k-1)}) = H_m^{(K)}$ or $g(H_m^{(k-1)}) = H_m^{(K)}$ needs only to be verified for each index value and for each bidding
20 device.

According to the seventh embodiment, each bidding device generates the bidding price information including select information for only indexes larger than the bidding price index k_m in the fifth embodiment, the
25 computational complexity can be reduced.

According to the eighth embodiment, since a desired bidding price is expressed by the sum of fractions Q of a price $F(k)$ corresponding to the index

k, an arbitrary price can be bid with a small number of indexes.

WHAT IS CLAIMED IS:

1. A quantitative competition method for a system in which a plurality of participant devices send their secret aimed values to a server device and said server device determines which of said plurality of participant devices has offered the maximum or minimum one of said aimed values received, said method comprising the steps wherein:

(a) each of said participant devices processes an initial value peculiar to said participant device with a predetermined one-way function by the number of times corresponding to said aimed value to generate aimed value information;

(b) either one of said each participant device and said server device processes said initial value with said one-way function to generate an updated initial value;

(c) said server device makes a check for matching between said updated aimed values and said aimed value information of said participant devices; and

(d) upon first detection of matching in said step (c), said server device decides that said aimed value of that one of said participant devices which corresponds to said updated value having matched said aimed value information is maximum or minimum.

2. The method of claim 1, further comprising a step of repeating the updating of said initial value in said step (b) and the check for matching in said step (c) when no matching is detected in said step (c).

3. The method of claim 2, wherein said step (b) includes a step of generating said updated initial value by said server device.

4. The method of claim 3, wherein: there is provided a conversion

table showing the relationships between a sequence of values selectable as said aimed values and a sequence of indexes k of integral values corresponding thereto;

said step (a) includes a step wherein, letting M be the number of participant devices, an m-th participant device m computes said aimed value information by

$$\gamma_m = g(h^{k_m}(IV_m))$$

where g is a one-way function, IV_m is said initial value, k_m is an index corresponding to said aimed value of said participant device m, and $h^{k_m}(IV_m)$ indicates that said initial value IV_m is processed with said one-way function h by k_m times;

said step (b) includes a step wherein said server device generates said updated initial value by

$$D_m = g(h^k(IV_m)); \text{ and}$$

said step (c) includes a step of making a check for said aimed value information $\gamma_m = D_m$.

5. The method of claim 2, wherein said step (b) includes a step wherein said each participant device generates said updated value by the number of times requested by said server device and sends said updated initial value to said server device.

6. The method of claim 5, wherein: there is provided a conversion table showing the relationships between a sequence of values selectable as said aimed values and a sequence of indexes k of integral values corresponding thereto; and

said step (a) includes the steps wherein:

(a-1) letting M be the number of participant devices, an m-th participant device m computes said aimed value information by

$$\gamma_m = g(h^{k_m}(IV_m))$$

where g is a one-way function, IV_m is said initial value, k_m is an index corresponding to said aimed value of said participant device m , and $h^{k_m}(IV_m)$ indicates that said initial value IV_m is processed with said one-way function h by k_m times;

(a-2) said each participant device generates verification information $C_m = h^{K+1}(IV_m)$ and sends it to said server device together with said aimed value information γ_m ; and

(a-3) said server device publishes said aimed value information γ_m and said verification information $C_m = h^{K+1}(IV_m)$ received from said each participant device on a bulletin board accessible from all of said participant devices.

7. The method of claim 6, wherein: said step (b) includes the steps wherein:

(b-1) said server device requests said each participant device to send $D_m = h^k(IV_m)$ corresponding to said index k ; and

(b-2) said each participant device responds to the request of said server device to generate $D_m = h^k(IV_m)$ corresponding to said index k as said updated initial value and sends it to said server; and

said step (c) includes a step of generating $g(D_m)$ and making a check for said aimed value information $\gamma_m = g(D_m)$.

8. The method of claim 7, wherein: said step (b) includes a step (b-0) wherein said server device sets said index k to an upper limit value K ; and

said step (c) includes the steps wherein said server device:

(c-1) publishes said $D_m = h^k(IV_m)$ received from said each participant device on said bulletin board;

(c-2) computes said $g(D_m)$ for said each participant device m ;

(c-3) makes a check to see if said $g(D_m)$ matches said aimed value information;

(c-4) if no match is detect for any of said m in said step (c-3), replaces said D_m with said C_m , decrementing said index k by one and returns to said step (b-1); and

(c-5) if a match is detected in said step (c-3), determines that the value corresponding to said index k at that time is said maximum or minimum aimed value.

9. The method of claim 8, wherein said step (c-1) includes a step wherein said server device generates $h(D_m)$ and makes a check to see if $h(D_m) = C_m$ holds.

10. The method of claim 8, wherein said step (c-5) includes a step wherein said server device publishes said determined maximum or minimum aimed value and said $h^{k_m}(IV_m)$ on said bulletin board.

11. The method of claim 5, wherein: there is provided a conversion table showing the relationships between a sequence of values selectable as said aimed values and a sequence of indexes k of integral values corresponding thereto; and

said step (a) includes the steps wherein:

(a-1) letting M be the number of participant devices, an m -th participant device m computes said aimed value information by

$$\gamma_m = g(h^{k_m}(IV_m))$$

where g is a one-way function, IV_m is said initial value, k_m is an index corresponding to said aimed value of said participant device m , and $h^{k_m}(IV_m)$

indicates that said initial value IV_m is processed with said one-way function h by k_m times;

(a-2) said each participant device generates verification information

$C_m = h^{K+1}(IV_m)$ and sends it to said server device together with said aimed value information γ_m ; and

- (a-3) said server device publishes said aimed value information γ_m and said verification information $C_m = h^{K+1}(IV_m)$ received from said each participant device on a bulleting board accessible from all of said participant devices;

said step (b) includes the steps wherein: said server device:

(b-0) said server device sets said index k to an upper limit value K ;

- (b-1) said server device inquires said each participant device m about whether said aimed value information corresponds to said index;

(b-2) said server device checks whether an answer from said each participant device acknowledges said correspondence;

- (b-3) if said answer from said each participant device denies said correspondence, said server device decrements said k by one and returns to said step (b-1);

(b-4) if said answer from said each participant device acknowledges said correspondence, said server device requests said each participant device to present an updated initial value $h^k(IV_m)$;

- (b-5) said each participant device generates $D_m = h^k(IV_m)$ using said initial value IV_m of its own and sends said D_m to said server device; and

(b-6) said server device publishes said D_m from said each participant device on said bulletin board; and

said step (c) includes the steps wherein said server device:

- (c-1) generates $h(D_m)$'s for all of said D_m 's received from all of said participant devices;

(c-2) checks whether said $h(D_m)$'s match said verification information C_m 's on said bulletin board, respectively;

(c-3) if no mismatch is detected in said step (c-1), generates $g(D_j)$ for D_j presented by a participant device j having bid;

(c-4) checks whether said $g(D_j)$ matches said aimed value information γ_j of said participant device j on said bulletin board; and

- 5 (c-5) if said $g(D_j)$ matches said γ_j in said step (c-4), decides that said participant device j sent to said server device said aimed value information corresponding to said aimed value k.

12. The method of claim 1, wherein: there is provided a conversion table showing the relationships between a sequence of values selectable as said aimed values and a sequence of indexes k of integral values corresponding thereto; and

said step (a) includes the steps wherein:

- (a-1) letting M be the number of participant devices, an m-th participant device m computes said aimed value information by
- 15 $\gamma_m = g(h^{k_m}(IV_m))$
- where g is a one-way function, IV_m is said initial value, k_m is an index corresponding to said aimed value of said participant device m, and $h^{k_m}(IV_m)$ indicates that said initial value IV_m is processed with said one-way function h by k_m times;

- 20 (a-2) said each participant device generates verification information $C_m = h^{K+1}(IV_m)$;

- (a-3) said each participant device m generates $h(PR_m(+)R_m)$ from a random number R_m and said aimed value PR_m and sends said $h(PR_m(+)R_m)$ to said server device together with said γ_m and said C_m , said (+) represents a
- 25 predetermined arbitrary operation;

said step (b) includes the steps wherein:

(b-1) said server device publishes its received γ_m , $h(PR_m(+)R_m)$ and

ID_m on said bulletin board;

(b-2) said server device requests said each participant device to present said aimed value PR_m and said random number R_m ;

(b-3) said each participant device sends said aimed value PR_m and said
5 random number R_m to said server device;

(b-4) said server device determines from its received PR_m and R_m an index k corresponding to the maximum one of said aimed values and a participant device j having sent said aimed value information corresponding to said index k ;

10 (b-5) said server device request all of said participant devices to present $h^k(IV_m)$; and

(b-6) said each participant device generates $D_m = h^k(IV_m)$ as said updated initial value using the initial value IV_m of its own, and sends said $D_m = h^k(IV_m)$ to said server device;

15 said step (c) includes the steps wherein said server device:

(c-1) publishes all of its received D_m 's on said bulletin board;

(c-2) generating $h(D_m)$'s for all of said D_m 's;

(c-3) checks whether said $h(D_m)$'s match said verification information C_m 's on said bulletin board, respectively;

20 (c-4) if no mismatch is detected in said step (c-3), generates $g(D_j)$ for D_j presented by said participant device j having sent said maximum aimed value determined in said step (b-4); and

(c-5) checks whether said $g(D_j)$ matches said aimed value information γ_j of said participant device j on said bulletin board; and

25 said step (d) includes a step wherein if a match is detected in said step (c-5), said server device decides that said participant device j sent said aimed value information for said aimed value k .

13. The method of claim 12, wherein said step (d) includes the steps of:

(d-1) generating $E_m = g(h^{t-k}(h^k(IV_m)))$ for t such that $k \leq t \leq K$ and for all of said m 's except said j ;

5 (d-2) checking whether these E_m 's match said aimed value information γ_m on said bulletin board; and

(d-3) if no match is detected in said step (d-2), deciding that said k is an index corresponding to the maximum or minimum aimed value, and outputting said k and said identifier ID_m of said participant device j having presented said aimed value.

14. The method of claim 12 or 13, wherein: said each participant device m adds to the computation using said aimed value PR_m and said random number R_m in said step (a-3) additional information I_m about said aimed value information by said each participant device m , and outputs

15 $h(PR_m(+)I_m(+)R_m)$; and

in said step (b-2) said server device requests all of said participant devices to present said additional information I_m as well as said aimed value PR_m and said random number R_m .

15. The method of claim 1, wherein: there is provided a conversion table showing the relationships between a sequence of values selectable as said aimed values and a sequence of indexes k of integral values respectively corresponding thereto;

said step (a) includes the steps wherein:

(a-1) each said bidding device generates $h(H_m^{(K)})$ as aimed value

25 information of said each participant device by repeating, for each of a sequence of index values k from at least k_m corresponding to an aimed value of said each participant device to an upper limit index value K , processing of:

combining an initial value of said each participant device with select information to provide combined information and

operating a one-way function h on said combined information to generate an updated value, said select information indicating whether said

5 each index value k is an aimed value or not; and

sends said aimed value information $H_m^{(K)}$ to said server device;

(a-2) said server device publishes said received aimed value information $H_m^{(K)}$ on a bulletin board accessible from all of said participant devices;

10 said step (b) includes the steps wherein:

(b-1) said server device requests said each participant device to send an updated initial value $\{H_m^{(k-1)}, b_m^{(k)}\}$ corresponding to each value of said index k in the descending order from K ; and

(b-2) said each participant device generates and sends $\{H_m^{(k-1)}, b_m^{(k)}\}$

15 as said updated initial value to said server device;

said step (c) includes the steps wherein said server device:

(c-1) publishes on said bulletin board said updated initial value $\{H_m^{(k-1)}, b_m^{(k)}\}$ received from said each participant device;

(c-2) processes said updated initial value $H_m^{(k)}$ with a one-way
20 function h to generate $H_m^{(k)} = h(H_m^{(k-1)} || b_m^{(k)})$;

(c-3) checks whether said updated initial value $H_m^{(k)}$ matches $H_m^{(k)}$ received previously; and

(c-4) if a match is detected in said step (c-3), decides whether said select information $b_m^{(k)}$ represents that the corresponding index k is the index
25 k_m of said aimed value; and

said step (d) is a step wherein if the result of decision in said step (c-4) is true, said server device outputs said index concerned and the corresponding

participant device number m , and if the result of decision is false, said server device returns to said step (b) and repeats processing for the next index value k .

16. The method of claim 1, wherein: there is provided a conversion table showing the relationships between a sequence of values selectable as said aimed values and a sequence of indexes k of integral values respectively corresponding thereto;

said step (a) includes the steps wherein:

(a-1) upon each processing of said initial value with said one-way function h , said each participant device generates an updated initial value by adding said processed initial value with select information $b_m^{(k)}$ indicating whether said processed initial value is an aimed value for one value of said index k , and generates $H_m^{(k)}$ by repeatedly performing this processing from at least that index k_m of a sequence of indexes which corresponds to said aimed value to the upper limit value K , and sends said $H_m^{(k)}$ as said aimed value information to said server device;

(a-2) said server device publishes its received aimed value information $H_m^{(K)}$ on a bulletin board accessible from all of said participant devices;

said step (b) includes the steps wherein:

(b-1) for each value of said index k in descending order from K , said server device inquires said each participant device about whether it has bid for said index k , and said each participant device responds YES or NO to said inquiry;

(b-2) upon first detection of the response YES, said server device requests said each participant device to send its updated initial value $H_m^{(k-1)}$, and

(b-3) said each participant device generates and sends $(H_m^{(k-1)} = h(H_m^{(k-1)}$

²⁾ $b_m^{(k-1)}$ as said updated initial value to said server device;

said step (c) includes the steps wherein said server device:

(c-1) publishes on said bulletin board said updated initial value ($H_m^{(k-1)}$) received from said each participant device;

5 (c-2) letting a and \underline{a} represent predetermined values of said select information $b_m^{(k)}$ indicating bidding and not bidding, respectively, generate, for said participant device m having bid for the current index k ,

$$H_m = h(\dots h(h(H_m^{(k-1)} || a) || \underline{a}) \dots || \underline{a})$$

through the use of said updated initial value $H_m^{(k-1)}$, and for every one of the

10 other participant devices m , generate

$$H_m = h(\dots h(h(H_m^{(k-1)} || \underline{a}) || a) \dots || a)$$

through the use of said updated initial values $H_m^{(k-1)}$,

(c-3) checks whether said H_m for said each participant device matches said $H_m^{(k)}$ published on said bulletin board; and

15 (c-4) if a match is detected in said step (c-3), determines that said participant device having responded YES is the winning bidding device, and publishes the current value of said index k as the index K_m of the aimed value of said winning bidding device.

17. The method of claim 1, wherein: there is provided a conversion
20 table showing the relationships between a sequence of values selectable as said aimed values and a sequence of indexes k of integral values respectively corresponding thereto, and let the initial value of said each participant device be represented by IV_m , where $m = 1, 2, \dots, M$, M being an integer equal to or greater than 2;

25 said step (a) is a step wherein said each participant device generates $H_m^{(K)} = h^{K-km}(g^{sm}(IV_m))$ using a predetermined positive integer x_m , said initial value IV_m and one-way functions h and g , and sends said $H_m^{(K)}$ as said aimed

value information to said server device;

said step (b) includes the steps wherein:

(b-1) said server device publishes said aimed value information A_m on a bulletin board accessible from all of said participant devices;

5 (b-2) said server device sends said index k to said each participant device to ask for its updated initial value;

(b-3) said each participant device decides whether its received index k is the index k_m corresponding to said aimed value;

(b-4) if the result of decision in step (b-3) is $k = k_m$, said each
10 participant device generates and sends $H_m^{(k-1)} = g^{xm-1}(IV_m)$ as said updated initial value to said server device; and

(b-5) if the result of decision in said step (b-3) is not $k = k_m$, said each participant device generates and sends $H_m^{(k-1)} = h^{k-km-1}(g^{xm}(IV_m))$ as said updated initial value to said server device;

15 said step (c) includes the steps wherein said server device:

(c-1) processes said updated initial value $H_m^{(k-1)}$ with said one-way function h to generate $h(H_m^{(k-1)})$;

(c-2) decides whether said $h(H_m^{(k-1)})$ is equal to said aimed value information $H_m^{(K)}$;

20 (c-3) if it is decided in said step (c-2) that they are equal, updates said aimed value information $H_m^{(K)}$ with said updated initial value $H_m^{(k-1)}$, then decrements said index k by one and return to said step (b-2);

(c-4) if it is decided in said step (c-2) that they are not equal, processes said updated initial value $H_m^{(k-1)}$ with said one-way function g to generate
25 $g(H_m^{(k-1)})$; and

(c-5) decides whether said $g(H_m^{(k-1)})$ matches said aimed value information $H_m^{(K)}$; and

said step (d) is a step wherein if a match is detected in said step (c-5), decides that the aimed value of said participant device corresponding to m and k having provided said match is the maximum or minimum.

18. The method of claim 1, wherein: there is provided a conversion
5 table showing the relationships between a sequence of values selectable as said aimed values and a sequence of indexes k of integral values respectively corresponding thereto;

said step (a) includes the steps wherein:

- (a-1), letting the initial value of said each participant device be
10 represented by IV_m , where $m = 1, 2, \dots, M$, M being an integer equal to or greater than 2, said each participant device generates $H_m^{(K)} = h^{K-km}(g^{xm}(IV_m))$ using a predetermined positive integer x_m , said initial value IV_m and one-way functions h and g , and sends said H_m as said aimed value information to said server device; and

- 15 (a-2) said server device publishes its received aimed value information $H_m^{(K)}$ on a bulletin board accessible from all of said participant devices;

said step (b) includes the steps wherein:

- (b-1) for each value of said index k in descending order from K , said server device inquires said each participant device about whether it has bid for
20 said index k , and said each participant device responds YES or NO to said inquiry;

(b-2) upon first detection of the response YES, said server device requests said each participant device to send its updated initial value $H_m^{(k-1)}$;

- (b-3) said each participant device decides whether its received k is the
25 index k corresponding to said aimed value;

(b-4) if the result of decision in said step (b-3) is $k = k_m$, said each participant generates and sends $H_m^{(k-1)} = g^{xm-1}(IV_m)$ as said updated initial

value to said server device; and

(b-5) if the result of decision in said step (b-3) is not $k = k_m$, said each participant device generates and sends $H_m^{(k-1)} = g^{x_{m-1}}(IV_m)$ as said updated initial value to said server device; and

5 said step (c) includes the steps wherein said server device:

(c-1) for said updated initial value $H_m^{(k-1)}$ received from said participant device having responded YES, generates

$$H_m = h^{K-km}g(H_m^{(k-1)})$$

and for said updated initial value received from said each participant device

10 having responded NO, generates

$$H_m = h^{K+1-k}g(H_m^{(k-1)})$$

(c-2) checks whether all of said H_m are equal to said aimed value information $H_m^{(K)}$ published on said bulletin board; and

(c-3) if it is decided in said step (c-2) that they are equal, determines
15 that said participant device having responded YES is the winning bidding device, and publishes the current value of said index k as the index k of the aimed value of said winning bidding device.

19. The method of claim 1, wherein: there is provided a conversion table showing the relationships between a sequence of values selectable as
20 said aimed values and a sequence of indexes k of integral values respectively corresponding thereto, and let the initial value of said each participant device be represented by IV_m , where $m = 1, 2, \dots, M$, M being an integer equal to or greater than 2;

said step (a) is a step wherein said each participant device generates
25 $H_m^{(K)} = h^{K-km}(g^{x_m}(IV_m))$ using a predetermined positive integer x_m , said initial value IV_m and one-way functions h and g , and sends said $H_m^{(K)}$ as said aimed value information to said server device;

said step (b) includes the steps wherein:

(b-1) said server device publishes said aimed value information $H_m^{(K)}$ on a bulletin board accessible from all of said participant devices;

(b-2) said server device sends said index k to said each participant
5 device to ask for its updated initial value;

(b-3) said each participant device decides whether its received index k is the index k_m corresponding to said aimed value;

(b-4) if the result of decision in step (b-3) is $k = k_m$, said each
participant device generates and $H_m^{(k-1)} = g^{xm-1}(IV_m)$ as said updated initial
10 value and sends it to said server device together with a flag indicating that
said k and k_m are equal; and

(b-5) if the result of decision in said step (b-3) is not $k = k_m$, said each
participant device generates and sends $H_m^{(k-1)} = h^{k-km-1}(g^{xm}(IV_m))$ as said
updated initial value to said server device;

15 said step (c) includes the steps wherein said server device:

(c-1) checks whether its received updated initial value $H_m^{(k-1)}$ is added
with said flag;

(c-2) if it is decided in said step (c-1) that said flag is added, processes
said updated initial value $H_m^{(k-1)}$ with said one-way function g to generate
20 $g(H_m^{(k-1)})$;

(c-3) decides whether said $g(H_m^{(k-1)})$ matches said aimed value
information $H_m^{(K)}$;

(c-4) if it is decided in said step (c-1) that no flag is added, processes
said updated initial value $H_m^{(k-1)}$ with said one-way function h to generate
25 $h(H_m^{(k-1)})$;

(c-5) decides whether said $h(H_m^{(k-1)})$ matches said aimed value
information $H_m^{(K)}$;

(c-6) if it is decided in said step that they are equal, updates said aimed value information $H_m^{(K)}$ with said initial value $H_m^{(k-1)}$, then decrements said index k by one and return to said step (b-2); and

(c-7) if it is decided in said step (c-5), processes said initial value $H_m^{(k-1)}$ with said one-way function g to generate $g(H_m^{(k-1)})$ and returns to said step (c-3); and

said step (d) is a step wherein if a match is detected in said step (c-3), decides that the aimed value of said participant device corresponding to m and k having provided said match is the maximum or minimum.

20 20. A quantitative competition method for a system in which a plurality of participant devices send their secret aimed values to a server device and said server device determines which of said plurality of participant devices has offered the maximum or minimum one of said aimed values received, and in which there is provided a conversion table showing the
15 relationships between a sequence of values selectable as said aimed values and a sequence of indexes k of integral values respectively corresponding thereto, and $m = 1, 2, \dots, M$, M being an integer equal to or greater than 2; said method comprising the steps wherein:

(a) each of said participant devices processes, with a predetermined
20 one-way function h and through the use of said conversion table, information $k(+)b_m^{(k)}(+)R_m^{(k)}$, which contains each index k equal to or larger than an index k_m corresponding to said aimed value, select information $b_m^{(k)}$ indicating whether said index k corresponds to said aimed value, and a random number $R_m^{(k)}$, to generate at least $K-k_m+1$ pieces of aimed value information
25 $h(k(+)b_m^{(k)}(+)R_m^{(k)})$, and sends these pieces of aimed value information to said server device, $A(+)B$ representing a predetermined arbitrary operation;

(b) said server device publishes its received aimed value information

on a bulletin board accessible from all of said participant devices;

(c) said server device obtains said random number R_m corresponding to each of said sequence of indexes k ;

(d) letting a be a predetermined value with which said select
5 information $b_m^{(k)}$ indicates said aimed value, said server device calculates $h(k(+)a(+))R_m^{(k)}$;

(e) said server device checks said aimed values on said bulletin board for matching with said calculated $h(k(+)a(+))R_m^{(k)}$; and

(f) if a match is detected in said step (e), said server device decides
10 that the aimed value of the aimed value information of a participant device having sent said random number $R_m^{(k)}$ at that time is the maximum or minimum value.

21. The method of claim 20, further comprising a step wherein if a match is detected in said step (d), said server device repeats said steps (c), (d)
15 and (e) for the next value of said index k .

22. The method of claim 21, wherein said step (c) includes the steps wherein: said server device requests said each participant device to send said random number $R_m^{(k)}$ corresponding to said index k ; said each participant device sends said requested random number $R_m^{(k)}$ to said server device; and
20 said server device receives said random number $R_m^{(k)}$.

23. The method of claim 21, wherein:

said step (a) includes a step wherein said each participant device sends said aimed value information $h(k(+)b_m^{(k)}(+))R_m^{(k)}$ to said server device together with said random number $R_m^{(k)}$;

25 said step (b) includes a step wherein said server device stores said random number $R_m^{(k)}$ in a nonpublic memory; and

said step (c) includes the steps wherein: said server device requests

said each participant device to send said random number $R_m^{(k)}$ corresponding to said index k ; said each participant device sends said requested random number $R_m^{(k)}$ to said server device; and said server device receives said random number $R_m^{(k)}$.

5 24. The method of claim 4, 12, 15, 16, 17, 18, 19 or 20 wherein said sequences of indexes k and values selectable as said aimed values are both monotonous increasing values in the same direction, and in said step (c) said server device determines the maximum aimed value.

10 25. The method of claim 4, 12, 15, 16, 17, 18, 19 or 20, wherein said sequences of indexes k and values selectable as said aimed values are both monotonous increasing values in opposite directions, and in said step (c) said server device determines the minimum aimed value.

15 26. The method of claim 4, 12, 15, 16, 17, 18, 19 or 20, wherein let an arbitrary aimed value be represented by $PR = F(k) + Q$, where $F(k)$ is a value in said conversion table corresponding to said index k and Q is a fraction which is a positive integer which satisfies $F(k+1) - F(k) > Q \geq 0$;

20 said step (a) includes a step wherein, letting said aimed value PR_m of said each participant device m be represented by $PR_m = F(k_m) + Q_m$, said each participant device m generates said aimed value information by processing said initial value with said one-way function h by the number of times corresponding to k_m , sends said aimed value information to said server device together with said fraction Q_m , where $m = 1, 2, \dots, M$, M being an integer equal to or greater than 2;

25 said step (b) includes a step wherein said server device publishes said aimed value information and said fraction Q_m on a bulletin board accessible from all of said participant devices;

 said step (c) includes a step where said server device makes a check

for matching between said updated initial value and said aimed value information for each index value in an ascending or descending order of said fraction Q_m where $m = 1, 2, \dots, M$; and

said step (d) includes a step wherein upon first detection of a match in
 5 said step (c), said server device finishes said check and determines, from k_m and m at the time of detecting the match, that $PR_m = F(k_m) + Q_m$ is said maximum or minimum aimed value.

27. The method of claim 1, 4, 12, 15, 16, 17, 18, 19 or 20, further comprising the steps wherein:

10 (0-1) said each participant device m sends its identifier ID_m to a provisional identifier registration device;

(0-2) said provisional identifier registration device issues a provisional identifier AID_m for said identifier ID_m , and stores said identifier ID_m and said provisional identifier AID_m in pair form in storage means;

15 (0-3) said provisional identifier registration device sends said provisional identifier AID_m to said each participant device; and

(0-4) said each participant device m sends said provisional identifier AID_m as said identifier to said server device, together with said aimed value information.

20

28. A participant device for a system in which M participant devices send their aimed values to a server device and said server device determines which of said M participant devices has offered the maximum or minimum one of said aimed values received, said participant device comprising:

25 aimed value generating means;

aimed value transforming means which processes said aimed value with a predetermined one-way function by the number of times corresponding

to said aimed value to obtain aimed value information; and

sending means for sending to said server device said aimed value information and an identifier specifying said participant device.

29. The participant device of claim 28, wherein said aimed value
5 transforming means comprises:

a conversion table for converting said aimed value PR_m to the corresponding index k_m ;

a one-way function h processor which processes an initial value IV_m inherent to said participant device with a one-way function h by the number
10 of times corresponding to said index k_m to obtain an output $h^{k_m}(IV_m)$; and
a one-way function g processor which processes said output from said one-way function h processor with a one-way function g to obtain said aimed value information.

30. The participant device of claim 29, further comprising verification
15 information generating means which generates $C_m = h^{K+1}(IV_m)$ as verification information by processing said initial value IV_m with said one-way function h $K+1$ times and sends said verification information C_m to said server device.

31. The participant device of claim 28, wherein said aimed value information transforming means comprises:
20 a memory in which there is stored a conversion table which defines the relationships between a sequence of monotone varying values selectable as aimed values and a sequence of indexes, for converting said aimed value PR_m to the corresponding index k_m ;

a one-way function h processor which processes an initial value
25 inherent to said participant device with a one-way function h by the number of time corresponding to said index k_m and outputs $h^{k_m}(IV_m)$; and

a one-way function g processor which processes the output from said

one-way function h processor with a one-way function g to obtain said aimed value information.

32. The participant device of claim 28, which further comprises: a random generator for generating a random number R_m ; an operating device
 5 for operating said random number R_m and said aimed value PR_m to obtain $PR_m(+)R_m$; one-way function h processing means for processing said $PR_m(+)R_m$ with a one-way function h to obtain $h(PR_m(+)R_m)$; and verification information generating means for processing said initial value IV_m with said one-way function h $K+1$ times to generate $C_m = h^{K+1}(IV_m)$; and wherein said
 10 $h(PR_m(+)R_m)$ and said verification information are sent to said server device together with said aimed value information.

33. The participant device of claim 28, wherein said aimed value transformer comprises:

a conversion table memory which has stored therein a conversion table
 15 which defines indexes $k = 1, 2, \dots, K$ corresponding to K kinds of values selectable as aimed values;

a select information generator which generates select information $b_m^{(k)}$ indicating whether to select an aimed value corresponding to each of said indexes $k = 1, 2, \dots, K$;

20 a random generator which generates a random number $R_m^{(k)}$ inherent to said participant device m and said index k ;

an operating device which receives said index k , said random number $R_m^{(k)}$ and said select information $b_m^{(k)}$ and performs an operation $k(+)b_m^{(k)}(+)R_m^{(k)}$;

25 a one-way function h processor which processes said $k(+)b_m^{(k)}(+)R_m^{(k)}$ with a one-way function h to obtain $h(k(+)b_m^{(k)}(+)R_m^{(k)})$; and

a control device which computes said $h(k(+)b_m^{(k)}(+)R_m^{(k)})$ for each of

said indexes k and provides the k pieces information as said aimed value information.

34. The participant device of claim 28, wherein said aimed value transformer comprises:

5 a conversion table memory which has stored therein a conversion table which defines indexes $k = 1, 2, \dots, K$ corresponding to K kinds of values selectable as aimed values, for converting said aimed value PR_m to the corresponding index k_m ;

10 initial value updating means which, for each index k , processes an initial value with a one-way function h and adds the processed initial value with select information $b_m^{(k)}$ for said index k to obtain an updated initial value and repeats this processing until $k = K$ is reached, thereby generating $H_m^{(K)}$;

15 K ;
select information generator which generates said select information $b_m^{(k)}$ whether said aimed value corresponds to each index k from at least k_m to

a one-way function h processor which processes said initial value with said one-way function h ;

a concatenator which concatenates said $H_m^{(k-1)}$ and said select information to generate $H_m^k = h(H_m^{(k-1)} || b_m^{(k)})$;

20 a buffer which temporarily holds the output from said concatenator and outputs said output for the next value of said index k ; and

a storage part which, for each value of said index k , stores $H_m^{(k)}$ corresponding thereto; and

25 wherein said sending means is a means which responds to a request of said server device for said index k to read out $H_m^{(k)}$ from said storage part and send said $H_m^{(k)}$ to said server device.

35. The participant device of claim 28, wherein said aimed value

transformer comprises:

a conversion table memory which has stored therein a conversion table which defines indexes $k = 1, 2, \dots, K$ corresponding to K kinds of values selectable as aimed values, for converting said aimed value PR_m to the

5 corresponding index k_m ;

a one-way function g processor which processes said initial value IV_m with a one-way function g by a predetermined number of times x_m to generate $g^{x_m}(IV_m)$;

10 a one-way function h processor which processes said $g^{x_m}(IV_m)$ with a one-way function h $K-k_m$ times to generate $H_m^{(K)} = h^{K-k_m}(g^{x_m}(IV_m))$ as said aimed value information; and

response generating means which responds to a request from said server device for k to decide whether $k=k_m$, and if true, generates $H_m^{(k-1)} = h^{k-km-1}(g^{x_m}(IV_m))$, and if false, generates $H_m^{(k-1)} = g^{x_m-1}(IV_m)$; and

15 wherein said sending means sends said $H_m^{(k-1)}$ in response to said request from said server device for said k .

36. The participant device of claim 28, wherein said aimed value transformer comprises:

20 a conversion table memory which has stored therein a conversion table which defines the relationships between a sequence of values selectable as said aimed values and a sequence of indexes k of integral values respectively corresponding thereto, for converting said aimed value PR_m to the corresponding index k_m ;

25 a fraction calculating part which, letting an arbitrary aimed value PR be represented by $PR = F(k)+Q$, where $F(k)$ is a value in said conversion table corresponding to said k and Q is a fraction which is a positive integer which satisfies $F(k+1)-F(k)>Q \geq 0$, calculates said fraction $Q_m = PR_m - F(k_m)$ based on

$F(k_m)$ obtained from said conversion table and said aimed value PR_m ; and

a one-way function h processor which processes said initial value IV_m with said one-way function h by the number of times corresponding to said k_m to generate said aimed value information; and

- 5 wherein said sending means sends said fraction Q_m to said server device together with said aimed value information.

37. A server device for a system in which M participant devices send their aimed values to said server device and said server device determines which of said M participant devices has offered the maximum or minimum

- 10 one of said aimed values received, said device comprising:

a conversion table memory which has stored therein a conversion table which defines the relationships between a sequence of values selectable as said aimed values and a sequence of indexes k of integral values respectively corresponding thereto, for converting said aimed value PR_m to the

- 15 corresponding index k_m ;

a bulletin board on which said server device writes said aimed value information an identifier received from each of said participant devices;

- 20 updated initial value generating means which generates an updated initial value by processing said initial value with a one-way function repeatedly in correspondence with values of an index k which is a predetermined consecutive positive integers;

a counter which updates said index k one by one; and

- 25 control means which, upon each updating of said index k , compares said updated initial value with said aimed value information on said bulletin board to check whether they match, and determines m and k at the time of first detection of a match.

38. The server device of claim 37, wherein: there are published on said

bulletin board $\gamma_m = g(h^{km}(IV_m))$ as said aimed value information;

said updated initial value generating means includes a one-way function g processor by which a response $D_m = h^k(IV_m)$ received from said participant device in correspondence with said index k is processed with a

5 one-way function g to generate $g(D_m)$ as said updated initial value; and

said control means makes a check to see if there exists on said bulleting board said aimed value information γ_m which matches said updated initial value $g(D_m)$.

39. The server device of claim 38, wherein there is published on said
10 bulletin board $C_m = h^{K+1}(IV_m)$ received from said participant device in advance, said server device further comprising a one-way function h processor which processes said response D_m with a one-way function h to generate $h(D_m)$, and

wherein said control means checks whether $C_m = h(D_m)$ holds, and if
15 not, rewrites said C_m with said D_m and updates said index k on said counter.

40. The server device of claim 37, wherein:

there are published on said bulletin board $C_m = h^{K+1}(IV_m)$, said aimed value information $\gamma_m = h^k(IV_m)$ and $h(PR_m(+)R_m)$ received from said each participant device, said PR_m and said R_m being an aimed value and a random
20 number of said each participant device m ;

said control means decides the maximum or minimum aimed value from said aimed values PR_m and said random numbers R_m received from said participant devices, and determines the index k_{mx} corresponding to said maximum or minimum aimed value and requests said each participant device
25 to send $D_m = h^{k_{mx}}(IV_m)$ corresponding to said index k_{mx} ;

said updated initial value generating means comprises a one-way function h processor for processing D_m with a one-way function h to generate

$h^{K+1-km_x}(D_m)$, and a one-way function g processor for processing D_j with a one-way function g to generate $g(D_j)$; and

said control means makes a check to see if said $h^{K+1-km_x}(D_m)$ matches C_m on said bulletin board and if said $g(D_j)$ matches said γ_m on said bulleting board;

41. The server device of claim 37, wherein:

there are published on said bulletin board $h(k(+)b_m^{(k)}(+)R_m^{(k)})$ together with said aimed value information γ_m received from said each participant device, said $b_m^{(k)}$ being select information whether said index k corresponds to its aimed value and said $R_m^{(k)}$ being a random number generated for said index k ;

said server device further comprises an operator for operating $k(+)b(+)R_m^{(k)}$, and a one-way function h processor for processing the result of said operation with a one-way function h to generate $h(k(+)b(+)R_m^{(k)})$, where b is a predetermined value which indicates that said select information $b_m^{(k)}$ has selected the aimed value corresponding to said index k ; and

said control means makes a check for matching between said $h(k(+)b(+)R_m^{(k)})$ and said $h(k(+)b_m^{(k)}(+)R_m^{(k)})$ on said bulletin board.

42. The server device of claim 37, wherein:

there is published on said bulletin board, as said aimed value information, $H_m^{(K)}$ generated by said each participant device which, upon each processing of said initial value with a one-way function h , added the processed value with select information $b_m^{(k)}$ indicating whether said value was an aimed value for each value of said index k and repeated this processing from at least the index k_m corresponding to said aimed value to the upper limit value K of said index k ;

said updated initial value generating means includes a one-way

function h processor by which $\{H_m^{(k-1)}, b_m\}$ received from said each participant device in answer to an inquiry for said index k is processed with a one-way function h to generate $H_m^{(k)} = h(H_m^{(k-1)} || b_m^{(k)})$; and

said server device includes an updated initial value comparator for

- 5 making a check to see if said $H_m^{(k)}$ matches previously received $H_m^{(k)}$.

43. The server device of claim 37, wherein: letting an arbitrary aimed value PR be represented by $PR = F(k) + Q$, where $F(k)$ is a value in said conversion table corresponding to said index k and Q is a fraction which is a positive integer which satisfies $F(k+1) - F(k) > Q \geq 0$, there is published on said

10 bulletin board said fraction Q received from said each participant device, together with said aimed value information;

said server device includes a sequencer for deciding the sequence of said fractions Q_m on said bulletin board;

said updated initial value generating means includes a one-way

- 15 function h processor for processing said initial value with a one-way function h by k times to generate $h^k(IV_m)$ and a one-way function g processor for processing said $h^k(IV_m)$ with a one-way function g to generate $D_m = g(h^k(IV_m))$; and

control means makes a check to see if said D_m matches said aimed

- 20 value information on said bulletin board in the sequence of said fractions Q_m .

44. The server device of claim 37, wherein there is published on said bulletin board $H_m^{(K)} = h^{K-km}(g^{xm}(IV_m))$ as said aimed value information received from said each participant device, which further comprises a one-way function h processor by which $H_m^{(k-1)}$ received from said each participant

25 device as an answer to an inquiry for said k is processed with a one-way function h to generate $h(H_m^{(k-1)})$, and a one-way function g processor for processing said answer $H_m^{(k-1)}$ with a one-way function g to generate $g(H_m^{(k-1)})$.

¹⁾); and

wherein said control means: makes a check to see if said $h(H_m^{(k-1)})$ matches said aimed value information $H_m^{(K)}$ published on said bulletin board; if a match is detected, updates said aimed value information $H_m^{(K)}$ with said $H_m^{(k-1)}$ and decrements said index k on said counter by one; and if a mismatch is detected, makes a check to see if said $g(H_m^{(k-1)})$ matches said aimed value information $H_m^{(K)}$; and if a match is detected, determines, based on k and m at that time, the maximum or minimum aimed value PR_m and the participant device m having offered said value PR_m .

45. The server device of claims 37, 38, 40, 41, 42, 43 or 44, wherein: letting an arbitrary aimed value PR be represented by $PR = F(k) + Q$, where $F(k)$ is a value in said conversion table corresponding to said index k and Q is a fraction which is a positive integer which satisfies $F(k+1) - F(k) > Q \geq 0$, there is published on said bulletin board said fraction Q received from said each participant device, together with said aimed value information;

said server device includes:

a sequencer for deciding the sequence of said fractions Q_m on said bulletin board; and

select information comparator for checking whether said select information $b_m^{(k)}$ is equal to a value b indicating the selection of the aimed value corresponding to said index k in said decided sequence of fractions Q_m .

46. The device of claim 29, 31, 33, 34, 36, 37, 40, 41, 43 or 44, wherein said sequence of index values k and said sequence of values selectable as said aimed values on said conversion table are monotone increasing values in the same direction, and said server device determines the maximum aimed value.

47. The device of claim 29, 31, 33, 34, 36, 37, 40, 41, 43 or 44,

wherein said sequence of index values k and said sequence of values selectable as said aimed values on said conversion table are monotone increasing values in opposite directions, and said server device determines the minimum aimed value.

5

48. A recording medium on which there is recorded as a program the procedure which is followed by an m -th one of M participant devices, where $m = 1, 2, \dots, M$, in a quantitative competition method for a system in which said M participant devices send their aimed values to a server device and said
 10 server device determines which of said M participant devices has offered the maximum or minimum one of said aimed values received, and there is provided a conversion table showing the relationships between a sequence of values selectable as said aimed values and a sequence of indexes k of integral values respectively corresponding thereto, said procedure comprising the
 15 steps of:

(a) processing an initial value inherent to said participant device m with a predetermined one-way function by the number of times corresponding to said aimed value to generate aimed value information

$$\gamma_m = g(h^{k_m}(IV_m))$$

20 where g is a one-way function, IV_m is said initial value, k_m is an index corresponding to the aimed value of said participant device m and $h^{k_m}(IV_m)$ indicates processing of said initial value IV_m with a one-way function h by k_m times; and

(b) sending said aimed value information $\gamma_m = g(h^{k_m}(IV_m))$ to said
 25 server device.

49. A recording medium on which there is recorded as a program the procedure which is followed by an m -th one of M participant devices, where

$m = 1, 2, \dots, M$, in a quantitative competition method for a system in which said M participant devices send their aimed values to a server device and said server device determines which of said M participant devices has offered the maximum or minimum one of said aimed values received, and there is

- 5 provided a conversion table showing the relationships between a sequence of values selectable as said aimed values and a sequence of indexes k of integral values respectively corresponding thereto, said procedure comprising the steps of:

- 10 (a-1) processing an initial value inherent to said participant device m with a predetermined one-way function by the number of times corresponding to said aimed value to generate aimed value information

$$\gamma_m = g(h^{k_m}(IV_m))$$

where g is a one-way function, IV_m is said initial value, k_m is an index corresponding to the aimed value of said participant device m and $h^{k_m}(IV_m)$

- 15 indicates processing of said initial value IV_m with a one-way function h by k_m times;

(a-2) generating verification information $C_m = h^{K+1}(IV_m)$ and sending said verification information to said server device together with said aimed value information γ_m ;

- 20 (b) generating said initial value updated by the number of times requested by said server device and sending said updated initial value to said server device; and

(c) sending said aimed value information $\gamma_m = g(h^{k_m}(IV_m))$ to said server device.

- 25 50. The recording medium of claim 49, wherein said step (b) includes a step of generating $D_m = h^k(IV_m)$ as said updated initial value corresponding to said index k and sending said updated initial value to said server device in

response to its request.

51. A recording medium on which there is recorded as a program the procedure which is followed by an m-th one of M participant devices, where $m = 1, 2, \dots, M$, in a quantitative competition method for a system in which
- 5 said M participant devices send their aimed values to a server device and said server device determines which of said M participant devices has offered the maximum or minimum one of said aimed values received, and there is provided a conversion table showing the relationships between a sequence of values selectable as said aimed values and a sequence of indexes k of integral
- 10 values respectively corresponding thereto, said procedure comprising the steps of:

(a-1) computing aimed value information by

$$\gamma_m = g(h^{k_m}(IV_m))$$

- where g is a one-way function, IV_m is said initial value, k_m is an index
- 15 corresponding to the aimed value PR_m of said participant device m and $h^{k_m}(IV_m)$ indicates processing of said initial value IV_m with a one-way function h by k_m times;

(a-2) generating verification information $C_m = h^{K+1}(IV_m)$;

- (a-3) generating $h(PR_m(+)R_m)$ from a random number R_m and said
- 20 aimed value PR_m and sending said $h(PR_m(+)R_m)$ to said server device together with said aimed value information γ_m and said verification information C_m , said (+) indicating a predetermined arbitrary operation;

(b-1) sending said aimed value PR_m and said random number R_m to said server device in response to its request; and

- 25 (b-2) generating $D_m = h^k(IV_m)$ as said updated initial value corresponding to said index k and sending said updated initial value to said server device in response to its request to present said $h^k(IV_m)$.

52. The recording medium of claim 51, wherein said step (a-3) is a step of generating $h(PR_m(+)R_m)$ from a random number R_m , said aimed value PR_m and additional information I_m about the sending of said aimed value information indicated by said participant device m and sending said
- 5 $h(PR_m(+)R_m)$ to said server device, said additional information I_m being sent to said server device in said step (b-2).

53. A recording medium on which there is recorded as a program the procedure which is followed by an m -th one of M participant devices, where $m = 1, 2, \dots, M$, in a quantitative competition method for a system in which
- 10 said M participant devices send their aimed values to a server device and said server device determines which of said M participant devices has offered the maximum or minimum one of said aimed values received, and there is provided a conversion table showing the relationships between a sequence of values selectable as said aimed values and a sequence of indexes k of integral
- 15 values respectively corresponding thereto, said procedure comprising the steps wherein:

- (a) upon each processing of said initial value with said one-way function h , said each participant device generates an updated initial value by adding said processed initial value with select information $b_m^{(k)}$ indicating
- 20 whether said processed initial value is an aimed value for one value of said index k , and generates $H_m^{(K)}$ by repeatedly performing this processing from at least that index k_m of a sequence of indexes which corresponds to said aimed value to the upper limit value K , and sends said $H_m^{(K)}$ as said aimed value information to said server device;
- 25 (b-1) said server device requests said each participant device to send an updated initial value $\{H_m^{(k-1)}, b_m^{(k)}\}$ corresponding to each value of said index k in descending order from K ; and

(b-2) said each participant device generates and sends $\{H_m^{(k-1)}, b_m^{(k)}\}$ as said updated initial value to said server device.

54. A recording medium on which there is recorded as a program the procedure which is followed by an m-th one of M participant devices, where $m = 1, 2, \dots, M$, in a quantitative competition method for a system in which said M participant devices send their aimed values to a server device and said server device determines which of said M participant devices has offered the maximum or minimum one of said aimed values received, and there is provided a conversion table showing the relationships between a sequence of values selectable as said aimed values and a sequence of indexes k of integral values respectively corresponding thereto, said procedure comprising the steps of:

(a) generating $H_m^{(K)} = h^{K-k_m}(g^{x_m}(IV_m))$ as said aimed value information using a predetermined positive integer x_m , an initial value IV_m and one-way functions h and g, and sends said aimed value information to said server device;

(b-1) decides whether its received index k from said server device is the index k_m corresponding to said aimed value;

(b-2) if the result of decision in step (b-1) is $k = k_m$, generating and sending $H_m^{(k-1)} = g^{x_m-1}(IV_m)$ as said updated initial value to said server device; and

(b-3) if the result of decision in said step (b-1) is not $k = k_m$, generating and sending $H_m^{(k-1)} = h^{k-k_m-1}(g^{x_m}(IV_m))$ as said updated initial value to said server device.

55. A recording medium on which there is recorded as a program the procedure which is followed by an m-th one of M participant devices, where $m = 1, 2, \dots, M$, in a quantitative competition method for a system in which

said M participant devices send their aimed values to a server device and said server device determines which of said M participant devices has offered the maximum or minimum one of said aimed values received, and there is provided a conversion table showing the relationships between a sequence of values selectable as said aimed values and a sequence of indexes k of integral values respectively corresponding thereto, letting the initial value of said each participant device be represented by IV_m , said procedure comprising the steps of:

(a) generating $H_m^{(K)} = h^{K-km}(g^{xm}(IV_m))$ as said aimed value information using a predetermined positive integer x_m , an initial value IV_m and one-way functions h and g, and sends said aimed value information to said server device;

(b-1) decides whether its received index k from said server device is the index k_m corresponding to said aimed value;

(b-2) if the result of decision in step (b-1) is $k = k_m$, generating $H_m^{(k-1)} = g^{xm-1}(IV_m)$ as said updated initial value and sending said updated initial value to said server device together with a flag indicating that said k and k_m are equal; and

(b-3) if the result of decision in said step (b-1) is not $k = k_m$, generating and sending $H_m^{(k-1)} = h^{k-km-1}(g^{xm}(IV_m))$ as said updated initial value to said server device.

56. A recording medium on which there is recorded as a program the procedure which is followed by an m-th one of M participant devices, where $m = 1, 2, \dots, M$, in a quantitative competition method for a system in which said M participant devices send their aimed values to a server device and said server device determines which of said M participant devices has offered the maximum or minimum one of said aimed values received, and there is

provided a conversion table showing the relationships between a sequence of values selectable as said aimed values and a sequence of indexes k of integral values respectively corresponding thereto, said procedure comprising the step of:

- 5 (a) processing, with a predetermined one-way function h and through the use of said conversion table, information $k(+)\mathbf{b}_m^{(k)}(+)\mathbf{R}_m^{(k)}$, which contains each index k equal to or larger than an index k_m corresponding to said aimed value, select information $\mathbf{b}_m^{(k)}$ indicating whether said index k corresponds to said aimed value, and a random number $\mathbf{R}_m^{(k)}$, to generate at least $K-k_m+1$
- 10 pieces of aimed value information $h(k(+)\mathbf{b}_m^{(k)}(+)\mathbf{R}_m^{(k)})$, and sends these pieces of aimed value information to said server device, $A(+)\mathbf{B}$ representing a predetermined arbitrary operation.

57. The recording medium of claim 56, wherein said procedure further comprises a step of sending to said server device a random number $\mathbf{R}_m^{(k)}$
- 15 corresponding to the index k received from said server device.

58. The recording medium of claim 56, wherein said step (a) includes a step of sending a random number $\mathbf{R}_m^{(k)}$ to said server device together with said $h(k(+)\mathbf{b}_m^{(k)}(+)\mathbf{R}_m^{(k)})$.

59. The recording medium of claim 49, 51, 53, 54, 55 or 56, wherein
- 20 let an arbitrary aimed value be represented by $\mathbf{PR} = \mathbf{F}(k)+\mathbf{Q}$, where $\mathbf{F}(k)$ is a value in said conversion table corresponding to said index k and \mathbf{Q} is a fraction which is a positive integer which satisfies $\mathbf{F}(k+1)-\mathbf{F}(k)>\mathbf{Q}\geq 0$;

- said procedure further comprises a step wherein, letting said aimed value \mathbf{PR}_m of said each participant device m be represented by $\mathbf{PR}_m =$
- 25 $\mathbf{F}(k_m)+\mathbf{Q}_m$, said each participant device m sends said fraction \mathbf{Q}_m to said server device together with said aimed value information γ_m .

60. The recording medium of claim 49, 51, 53, 54, 55 or 56, wherein

said sequences of indexes k and values selectable as said aimed values are both monotonous increasing values in the same direction.

61. The recording medium of claim 49, 51, 53, 54, 55 or 56, wherein said sequences of indexes k and values selectable as said aimed values are both monotonous increasing values in opposite directions.

62. The recording medium of claim 49, 51, 53, 54, 55 or 56, wherein said procedure further comprises the steps of:

(0-1) sending the identifier ID_m of said each participant device to a provisional identifier registration device;

10 (0-2) receiving a provisional identifier AID_m from said provisional identifier registration device; and

(0-3) sending said provisional identifier AID_m as an identifier to said server device together with said aimed value information.

15 63. A recording medium on which there is recorded as a program the procedure which is followed by a server device in a quantitative competition method for a system in which a plurality of participant devices send their aimed values to said server device and said server device determines which of said participant devices has offered the maximum or minimum one of said aimed values received, and there is provided a conversion table showing the relationships between a sequence of values selectable as said aimed values and a sequence of indexes k of integral values respectively corresponding thereto, said procedure comprising the steps of:

25 (a) publishing aimed value information $\gamma_m = g(h^{k_m}(IV_m))$ received from said each participant device on a bulletin board accessible from all of said participant device, g being a one-way function, IV_m being said initial value, k_m being an index corresponding to the aimed value of said each participant

device m and $h^{k_m}(IV_m)$ indicating processing of said initial value IV_m with a one-way function h by k_m times;

(b) generating an updated initial value by $D_m = g(h^k(IV_m))$;

(c) checking whether there is any aimed value information γ_m which is equal to said updated initial value D_m ; and

(d) upon first detection of a match in said step (c), deciding that the aimed value of the participant device corresponding to said updated initial value D_m which matches said aimed value information γ_m .

64. The recording medium of claim 63, wherein said step (a) includes a step of publishing verification information $C_m = h^{K+1}(IV_m)$ received from said each participant device on said bulletin board together with said aimed value information γ_m .

65. The recording medium of claim 64, wherein: said step (b) includes the steps of:

(b-1) requesting said each participant device to send $D_m = h^k(IV_m)$ corresponding to said index k ; and

(b-2) receiving from said each participant device $D_m = h^k(IV_m)$ as said updated initial value corresponding to said index k ; and

said step (c) includes a step of generating $g(D_m)$ and making a check for said aimed value information $\gamma_m = g(D_m)$.

66. The recording medium of claim 65, wherein:

said step (b) includes a step (b-0) of setting said index k to an upper limit value K ; and

said step (c) includes the steps of:

(c-1) publishing said $D_m = h^k(IV_m)$ received from said each participant device on said bulletin board;

(c-2) computing said $g(D_m)$ for said each participant device m ;

(c-3) making a check to see if said $g(D_m)$ matches said aimed value information;

(c-4) if no match is detected for any of said m in said step (c-3), replacing said D_m with said C_m , decrementing said index k by one and returning to said step (b-1); and

(c-5) if a match is detected in said step (c-3), determining that the value corresponding to said index k at that time is said maximum or minimum aimed value.

67. The recording medium of claim 66, wherein said step (c-1) includes a step of generating $h(D_m)$ and making a check to see if $h(D_m) = C_m$ holds.

68. The recording medium of claim 66, wherein said procedure includes a step of publishing said determined maximum or minimum aimed value and said $h^{km}(IV_m)$ on said bulletin board.

69. The recording medium of claim 63, wherein:

said step (b) includes the steps of

(b-0) setting said index k to an upper limit value K ;

(b-1) inquiring said each participant device m about whether said aimed value information corresponds to said index;

(b-2) checking whether an answer from said each participant device acknowledges said correspondence;

(b-3) if said answer from said each participant device denies said correspondence, decrementing said k by one and returning to said step (b-1);

(b-4) if said answer from said each participant device acknowledges said correspondence, requesting said each participant device to present an updated initial value $h^k(IV_m)$;

(b-5) publishing $D_m = h^k(IV_m)$ from said each participant device on

said bulletin board; and

said step (c) includes the steps of:

(c-1) generating $h(D_m)$'s for all of said D_m 's;

(c-2) checking whether said $h(D_m)$'s match said verification

5 information C_m 's on said bulletin board, respectively;

(c-3) if no mismatch is detected in said step (c-1), generating $g(D_j)$ for D_j presented by a participant device j having bid;

(c-4) checking whether said $g(D_j)$ matches said aimed value information γ_j of said participant device j on said bulletin board; and

10 (c-5) if said $g(D_j)$ matches said γ_j in said step (c-4), decides that said participant device j sent to said server device said aimed value information corresponding to said aimed value k.

70. The recording medium of claim 63, wherein:

said step (b) includes the steps of:

15 (b-1) publishing its received γ_m , $h(PR_m(+))R_m$ and ID_m on said bulletin board, said (+) indicating a predetermined arbitrary operation;

(b-2) requesting said each participant device to present its aimed value PR_m and random number R_m ;

(b-3) determining from its received PR_m and R_m an index k
20 corresponding to the maximum one of said aimed values and a participant device j having sent said aimed value information corresponding to said index k;

(b-4) requesting all of said participant devices to present $h^k(IV_m)$; and

(b-5) receiving $D_m = h^k(IV_m)$ as said updated initial value from said

25 each participant device;

said step (c) includes the steps of:

(c-1) publishing all of its received D_m 's on said bulletin board;

(c-2) generating $h(D_m)$'s for all of said D_m 's;

(c-3) checking whether said $h(D_m)$'s match said verification information C_m 's on said bulletin board, respectively;

(c-4) if no mismatch is detected in said step (c-3), generating $g(D_j)$ for
 5 D_j presented by said participant device j having sent said maximum aimed value determined in said step (b-4); and

(c-5) checking whether said $g(D_j)$ matches said aimed value information γ_j of said participant device j on said bulletin board; and

said step (d) includes a step of deciding that said participant device j
 10 sent said aimed value information for said aimed value k, if a match is detected in said step (c-5).

71. The recording medium of claim 70, wherein said step (d) includes the steps of:

(d-1) generating $E_m = g(h^{t-k}(h^k(IV_m)))$ for t such that $k \leq t \leq K$ and for all
 15 of said m 's except said j;

(d-2) checking whether these E_m 's match said aimed value information γ_m on said bulletin board; and

(d-3) if no match is detected in said step (d-2), deciding that said k is an index corresponding to the maximum or minimum aimed value, and
 20 outputting said k and said identifier ID_m of said participant device j having presented said aimed value.

72. The recording medium of claim 70 or 71, wherein

said step (b-2) includes a step of requesting all of said participant devices to present additional information I_m as well as said aimed value PR_m
 25 and said random number R_m .

73. A recording medium on which there is recorded as a program the procedure which is followed by a server device in a quantitative competition

method for a system in which a plurality of participant devices send their aimed values to said server device and said server device determines which of said participant devices has offered the maximum or minimum one of said aimed values received, and there is provided a conversion table showing the relationships between a sequence of values selectable as said aimed values and a sequence of indexes k of integral values respectively corresponding thereto, said procedure comprising the steps of:

(a) receiving, from each of participant devices, $h(H_m^{(k)})$ generated as aimed value information of said each participant device by repeating, for each of a sequence of index values k from at least k_m corresponding to an aimed value of said each participant device to an upper limit index value K , processing of:

combining an initial value of said each participant device with select information to provide combined information and

operating a one-way function h on said combined information to generate an updated value, said select information indicating whether said each index value k is an aimed value or not, and publishing said aimed value information $h(H_m^{(k)})$ on a bulletin board accessible from all of said participant devices and any other devices as well;

(b) requesting said each participant device to send an updated initial value $\{H_m^{(k-1)}, b_m^{(k)}\}$ corresponding to each value of said index k in descending order from K ;

(c) publishing said updated initial value $\{H_m^{(k-1)}, b_m^{(k)}\}$ on said bulletin board;

(d) processing said updated initial value $\{H_m^{(k-1)}, b_m^{(k)}\}$ with said one-way function h to generate $H_m^{(k)} = h(H_m^{(k-1)} || b_m^{(k)})$;

(e) checking whether said updated initial value $H_m^{(k)}$ matches $H_m^{(k)}$ in

$\{H_m^{(k)}, b_m^{(k+1)}\}$ received previously; and

(f) if a match is detected in said step (e), deciding whether said select information $b_m^{(k)}$ represents that the corresponding index k is the index k_m of said aimed value; and

- 5 (g) if the result of decision in said step (f) is true, outputting said index k concerned and the corresponding participant device number m , and if the result of decision is false, said server device returns to said step (b) and repeats processing for the next index value k .

74. A recording medium on which there is recorded as a program the
10 procedure which is followed by a server device in a quantitative competition method for a system in which a plurality of participant devices send their aimed values to said server device and said server device determines which of said participant devices has offered the maximum or minimum one of said aimed values received, and there is provided a conversion table showing the
15 relationships between a sequence of values selectable as said aimed values and a sequence of indexes k of integral values respectively corresponding thereto, said procedure comprising the steps wherein said server device:

- (a) receives $H_m^{(K)}$ as said aimed value information from said each participant device which, upon each processing of said initial value with said
20 one-way function h , generates an updated initial value by adding said processed initial value with select information $b_m^{(k)}$ indicating whether said processed initial value is an aimed value for one value of said index k , and generates $H_m^{(K)}$ by repeatedly performing this processing from at least that index k_m of a sequence of indexes which corresponds to said aimed value to
25 the upper limit value K , and publishes said aimed value information $H_m^{(K)}$ on a bulletin board accessible from all of said participant device;

- (b) for each value of said index k in order descending from K , inquires

said each participant device about whether it has bid for said index k , said each participant device responding YES or NO to said inquiry;

(c) upon first detection of the response YES, requests said each participant device to send its updated initial value $H_m^{(k-1)}$; and

- 5 (d) receives $H_m^{(k-1)} = h(H_m^{(k-2)} || b_m^{(k-1)})$ as said updated initial value from said each participant device and publishes said received updated initial value on said bulletin board;

- (e) letting a and \bar{a} represent predetermined values of said select information $b_m^{(k)}$ indicating bidding and not bidding, respectively, generates,
10 for said participant device m having bid for the current index k ,

$$H_m = h(\dots h(h(H_m^{(k-1)} || a) || \bar{a}) \dots || a)$$

through the use of said updated initial value $H_m^{(k-1)}$, and for every one of the other participant devices m , generates

$$H_m = h(\dots h(h(H_m^{(k-1)} || \bar{a}) || a) \dots || \bar{a})$$

- 15 through the use of said updated initial values $H_m^{(k-1)}$,

(f) checks whether said H_m for said each participant device matches said $H_m^{(k)}$ published on said bulletin board; and

- (g) if a match is detected in said step (f), determines that said participant device having responded YES is the winning bidding device, and
20 publishes the current value of said index k as the index k_m of the aimed value of said winning bidding device.

75. A recording medium on which there is recorded as a program the procedure which is followed by a server device in a quantitative competition method for a system in which a plurality of participant devices send their
25 aimed values to said server device and said server device determines which of said participant devices has offered the maximum or minimum one of said aimed values received, and there is provided a conversion table showing the

relationships between a sequence of values selectable as said aimed values and a sequence of indexes k of integral values respectively corresponding thereto, said procedure comprising the steps of:

- (a) letting the initial value of said each participant device be represented by IV_m , receiving from said each participant device $H_m^{(K)} = h^{K-km}(g^{xm}(IV_m))$ generated as said aimed value information using a predetermined positive integer x_m , said initial value IV_m and one-way functions h and g ;
- (b) publishing said aimed value information A_m on a bulletin board accessible from all of said participant devices; and
- 10 (c) sending said index k to said each participant device to ask for its updated initial value;
- (d) processing said updated initial value $H_m^{(k-1)}$ with said one-way function h to generate $h(H_m^{(k-1)})$;
- (e) deciding whether said $h(H_m^{(k-1)})$ is equal to said aimed value
- 15 information $H_m^{(K)}$;
- (f) if it is decided in said step (e) that they are equal, updating said aimed value information $H_m^{(K)}$ with said updated initial value $H_m^{(k-1)}$, then decrementing said index k by one and returning to said step (c);
- (g) if it is decided in said step (e) that they are not equal, processing
- 20 said updated initial value $H_m^{(k-1)}$ with said one-way function g to generate $g(H_m^{(k-1)})$; and
- (h) deciding whether said $g(H_m^{(k-1)})$ matches said aimed value information $H_m^{(K)}$; and
- (i) deciding that the aimed value of said participant device
- 25 corresponding to m and k having provided said match is the maximum or minimum, if a match is detected in said step (h).

76. A recording medium on which there is recorded as a program the

procedure which is followed by a server device in a quantitative competition method for a system in which a plurality of participant devices send their aimed values to said server device and said server device determines which of said participant devices has offered the maximum or minimum one of said aimed values received, and there is provided a conversion table showing the relationships between a sequence of values selectable as said aimed values and a sequence of indexes k of integral values respectively corresponding thereto, said procedure comprising the steps wherein said server device:

- (a), letting the initial value of said each participant device be represented by IV_m , where $m = 1, 2, \dots, M$, M being an integer equal to or greater than 2, receives from each participant device, as said aimed value information, $H_m^{(K)} = h^{K-km}(g^{xm}(IV_m))$ using a predetermined positive integer x_m , said initial value IV_m and one-way functions h and g , and publishes said received aimed value information on a bulletin board accessible from all of said participant devices;

(b) for each value of said index k in order descending from K , inquires said each participant device about whether it has bid for said index k , said each participant device responding YES or NO to said inquiry;

- (c) upon first detection of the response YES, requests said each participant device to send its updated initial value $H_m^{(k-1)}$;

(d) receives from said each participant device $H_m^{(k-1)} = g^{xm-1}(IV_m)$ if $k = k_m$ and $H_m^{(k-1)} = h^{k-km-1}(g^{xm}(IV_m))$ if $k \neq k_m$;

(e) for said updated initial value $H_m^{(k-1)}$ received from said participant device having responded YES, generates

$$H_m = h^{K-km}g(H_m^{(k-1)})$$

and for said updated initial value received from said each participant device having responded NO, generates

$$H_m = h^{K+1-k} g(H_m^{(k-1)})$$

(f) checks whether said H_m for said each participant device matches said $H_m^{(K)}$ published on said bulletin board; and

- (g) if a match is detected in said step (f), determines that said
 5 participant device having responded YES is the winning bidding device, and publishes the current value of said index k as the index K_m of the aimed value of said winning bidding device.

77. A recording medium on which there is recorded as a program the procedure which is followed by a server device in a quantitative competition
 10 method for a system in which a plurality of participant devices send their aimed values to said server device and said server device determines which of said participant devices has offered the maximum or minimum one of said aimed values received, and there is provided a conversion table showing the relationships between a sequence of values selectable as said aimed values
 15 and a sequence of indexes k of integral values respectively corresponding thereto, said procedure comprising the steps of:

- (a) letting the initial value of said each participant device be represented by IV_m , receiving from said each participant device $H_m^{(K)} = h^{K-km}(g^{xm}(IV_m))$ generated as said aimed value information using a predetermined
 20 positive integer x_m , said initial value IV_m and one-way functions h and g ;

(b) publishing said aimed value information $H_m^{(K)}$ on a bulletin board accessible from all of said participant devices; and

- (c) sending said index k to said each participant device to ask for its updated initial value;
 25 (d) checking whether its received updated initial value $H_{k,m}$ is added with said flag;
 (e) if it is decided in said step (d) that said flag is added, processing

said updated initial value $H_m^{(k-1)}$ with said one-way function g to generate $g(H_m^{(k-1)})$;

(f) deciding whether said $g(H_m^{(k-1)})$ matches said aimed value information $H_m^{(K)}$;

5 (g) if it is decided in said step (d) that no flag is added, processing said updated initial value $H_m^{(k-1)}$ with said one-way function h to generate $h(H_m^{(k-1)})$;

(h) deciding whether said $h(H_m^{(k-1)})$ matches said aimed value information $H_m^{(K)}$;

10 (i) if it is decided in said step that they are equal, updating said aimed value information $H_m^{(K)}$ with said initial value $H_m^{(k-1)}$, then decrementing said index k by one and returning to said step (c); and

(j) if it is decided in said step (h), processing said initial value $H_m^{(k-1)}$ with said one-way function g to generate $g(H_m^{(k-1)})$ and returning to said step

15 (f); and

(k) if a match is detected in said step (f), deciding that the aimed value of said participant device corresponding to m and k having provided said match is the maximum or minimum.

78. A recording medium on which there is recorded as a program the
 20 procedure which is followed by a server device in a quantitative competition method for a system in which a plurality of participant devices send their aimed values to said server device and said server device determines which of said participant devices has offered the maximum or minimum one of said aimed values received, and there is provided a conversion table showing the
 25 relationships between a sequence of values selectable as said aimed values and a sequence of indexes k of integral values respectively corresponding thereto, and $m = 1, 2, \dots, M$, M being an integer equal to or greater than 2;

said procedure comprising the steps of:

- (a) receiving from each of said participant devices at least $K - k_m + 1$ pieces of aimed value information $h(k(+)b_m^{(k)}(+)R_m^{(k)})$ generated by processing, with a predetermined one-way function h and through the use of
 5 said conversion table, information $k(+)b_m^{(k)}(+)R_m^{(k)}$, which contains each index k equal to or larger than an index k_m corresponding to said aimed value, select information $b_m^{(k)}$ indicating whether said index k corresponds to said aimed value, and a random number $R_m^{(k)}$, $A(+)B$ representing a predetermined arbitrary operation between A and B ;
- 10 (b) receiving and publishing said aimed value information on a bulletin board accessible from all of said participant devices;
- (c) obtaining said random number R_m corresponding to each of said sequence of indexes k ;
- (d) calculating $h(k(+)a(+)R_m^{(k)})$, where a is a predetermined value with
 15 which said select information $b_m^{(k)}$ indicates said aimed value;
- (e) checking said aimed values on said bulletin board for matching with said calculated $h(k(+)a(+)R_m^{(k)})$; and
- (f) if a match is detected in said step (e), deciding that the aimed value of the aimed value information of a participant device having sent said
 20 random number $R_m^{(k)}$ at that time is the maximum or minimum value.

79. The recording medium of claim 78, wherein said procedure further comprises a step of repeating said steps (c), (d) and (e) if a match is detected in said step (d).

80. The recording medium of claim 79, wherein said step (c) includes
 25 the steps of: requesting said each participant device to send said random number $R_m^{(k)}$ corresponding to said index k ; and receiving said random number $R_m^{(k)}$ from said each participant device.

81. The recording medium of claim 79, wherein:

said step (a) includes a step of receiving said random number $R_m^{(k)}$ sent from said each participant device together with said aimed value information $h(k(+)b_m^{(k)}(+)R_m^{(k)})$;

5 said step (b) includes a step of storing said random number $R_m^{(k)}$ in a nonpublic memory; and

said step (c) includes the steps of: requesting said each participant device to send said random number $R_m^{(k)}$ corresponding to said index k; and receiving said random number $R_m^{(k)}$ from said each participant device.

10 82. The recording medium of claim 63, 64, 69, 70, 73, 74, 75, 76, 77 or 78, wherein said sequences of indexes k and values selectable as said aimed values are both monotonous increasing values in the same direction, and in said step (c) said server device determines the maximum aimed value.

15 83. The recording medium of claim 63, 64, 69, 70, 73, 74, 75, 76, 77 or 78, wherein said sequences of indexes k and values selectable as said aimed values are both monotonous increasing values in opposite directions, and in said step (c) said server device determines the minimum aimed value.

20 84. The recording medium of claim 63, 64, 69, 70, 73, 74, 75, 76, 77 or 78, wherein let an arbitrary aimed value be represented by $PR = F(k)+Q$, where $F(k)$ is a value in said conversion table corresponding to said index k and Q is a fraction which is a positive integer which satisfies $F(k+1)-F(k)>Q\geq 0$;

25 said step (a) includes a step wherein, letting said aimed value PR_m of said each participant device m be represented by $PR_m = F(k_m)+Q_m$, said server device receives from each participant device m said aimed value information generated by processing said initial value with said one-way function h by the number of times corresponding to k_m , together with said fraction Q_m , where m

= 1, 2, ..., M, said M being an integer equal to or greater than 2, and said server device publishes said aimed value information and said fraction Q_m on a bulletin board accessible from all of said participant devices;

- 5 said step (c) includes a step where said server device makes a check for matching between said updated initial value and said aimed value information for each index value in an ascending or descending order of said fraction Q_m where $m = 1, 2, \dots, M$; and

- 10 said step (d) includes a step wherein, upon first detection of a match in said step (c), said server device finishes said check and determines, from k_m and m at the time of detecting the match, that $PR_m = F(k_m) + Q_m$ is said maximum or minimum aimed value.

85. The recording medium of claim 78 or 79, wherein let an arbitrary aimed value be represented by $PR = F(k) + Q$, where $F(k)$ is a value in said conversion table corresponding to said index k and Q is a fraction which is a
15 positive integer which satisfies $F(k+1) - F(k) > Q \geq 0$;

 said step (a) includes a step wherein, letting said aimed value PR_m of said each participant device m be represented by $PR_m = F(k_m) + Q_m$, said server device receives said fraction Q_m together with said aimed value information;

- 20 said step (b) includes a step of publishing said fraction Q_m on said bulletin board together with said aimed value information, where $m = 1, 2, \dots, M$, said M being an integer equal to or greater than 2;

 said step (e) includes a step of making said check for matching for each index value in an ascending or descending order of said fraction Q_m where $m = 1, 2, \dots, M$; and

- 25 said step (f) includes a step wherein, upon first detection of a match in said step (c), said server device finishes said check and determines, from k_m and m at the time of detecting the match, that $PR_m = F(k_m) + Q_m$ is said

maximum or minimum aimed value.

86. A quantitative competition system which comprises a server device and M participant devices each connected via a communication channel to said server device and in which said M participant devices send their aimed values to said server device and said server device determines which of said M participant devices has offered the maximum or minimum one of said aimed values received,
- each of said participant devices comprising:
- 10 aimed value generating means for generating an aimed value PR_m ;
- aimed value transforming means provided with a conversion table memory having stored therein a conversion table which defines the relationships between a sequence of values selectable as said aimed values and a sequence of indexes corresponding thereto, for converting said aimed
- 15 value PR_m to the corresponding index k_m and which processes said aimed value with a predetermined one-way function by the number of times corresponding to said aimed value to obtain aimed value information; and
- sending means for sending to said server device said aimed value information and an identifier identifying said participant device; and
- 20 said server device comprising:
- a conversion table memory which has stored therein a conversion table which is the same as said conversion table;
- a bulletin board on which said server device writes said aimed value information an identifier received from said each participant device;
- 25 updated initial value acquiring means which acquires an updated initial value obtained by processing said initial value with a one-way function repeatedly in correspondence with values of an index k which is a

predetermined consecutive positive integers;

a counter which updates said index k one by one; and

control means which, upon each updating of said index k , compares said updated initial value with said aimed value information on said bulletin board to check whether they match, and determines m and k at the time of first detection of a match.

87. The system of claim 86, wherein said each participant device has initial value updating means for processing said initial value with a one-way function h to generate an updated initial value and for sending said updated initial value to said server device, and said updated initial value acquiring means of said server device receives said updated initial value from said each participant device.

88. The system of claim 86, wherein said updated initial value acquiring means of said server device processes said initial value with a one-way function h to generate said updated initial value.

89. The system of claim 87 or 88, wherein said aimed value transformer of said each participant device comprises:

a one-way function h processor which processes an initial value IV_m inherent to said participant device with a one-way function h by the number of times corresponding to said index k_m to obtain an output $h^{k_m}(IV_m)$; and

a one-way function g processor which processes said output from said one-way function h processor with a one-way function g to obtain said aimed value information.

90. The system of claim 89, wherein said aimed value transformer of said each participant device includes verification information generating means for processing said initial value IV_m with said one-way function h by $K+1$ times to generate $C_m = h^{K+1}(IV_m)$ as verification information and for

wherein there is published on said bulletin board $C_m = h^{K+1}(IV_m)$ received from said each participant device in advance, said server device further comprising a one-way function h processor which processes said

wherein said control means checks whether $C_m = h(D_m)$ holds, and if not, rewrites said C_m with said D_m and updates said index k on said counter.

10 a random generator for generating a random number R_m ;
 an operating device for operating said random number R_m and said
 aimed value PR_m to obtain $PR_m(+)R_m$, where $(+)$ represents a predetermined
 arbitrary operation;

verification information generating means for processing said initial value IV_m with said one-way function h $K+1$ times to generate $C_m = h^{K+1}(IV_m)$; and wherein:

said $h(PR_m(+)R_m)$ and said verification information are sent to said server device together with said aimed value information;

there are published on said bulletin board $C_m = h^{K+1}(IV_m)$, said aimed value information $\gamma_m = h^k(IV_m)$ and $h(PR_m(+)R_m)$ received from said each participant device, said PR_m and said R_m being an aimed value and a random

said control means decides the maximum or minimum aimed value
from said aimed values PR_m and said random numbers R_m received from said

participant devices, and determines the index k_{mx} corresponding to said maximum or minimum aimed value and requests said each participant device to send $(D_m) = h^{k_{mx}}(IV_m)$ corresponding to said index k_{mx} ;

- said updated initial value acquiring means comprises a one-way
 5 function h processor for processing D_m with a one-way function h to generate $h^{K+1-k_{mx}}(D_m)$, and a one-way function g processor for processing D_j with a one-way function g to generate $g(D_j)$; and

- said control means makes a check to see if said $h^{K+1-k_{mx}}(D_m)$ matches C_m on said bulletin board and if said $g(D_j)$ matches said γ_m on said bulleting
 10 board.

92. The system of claim 86, wherein said aimed value transformer of said each participant device comprises:

- a conversion table memory which has stored therein a conversion table which defines indexes $k = 1, 2, \dots, K$ corresponding to K kinds of values
 15 selectable as aimed values;

a select information generator which generates select information $b_m^{(k)}$ indicating whether to select an aimed value corresponding to each of said indexes $k = 1, 2, \dots, K$;

- a random generator which generates a random number $R_m^{(k)}$ inherent
 20 to said participant device m and said index k ;

an operating device which receives said index k , said random number $R_m^{(k)}$ and said select information $b_m^{(k)}$ and performs an operation $k(+)b_m^{(k)}(+)R_m^{(k)}$,

- a one-way function h processor which processes said $k(+)b_m^{(k)}(+)R_m^{(k)}$
 25 with a one-way function h to obtain $h(k(+)b_m^{(k)}(+)R_m^{(k)})$; and

a control device which computes said $h(k(+)b_m^{(k)}(+)R_m^{(k)})$ for each of said indexes k and provides the k pieces information as said aimed value

information;

in said server device:

there are published on said bulletin board $h(k(+)b_m^{(k)}(+)R_m^{(k)})$ together with said aimed value information γ_m received from said each participant

5 device;

said server device further comprises an operator for operating $k(+)b(+)R_m^{(k)}$, and

a one-way function h processor for processing the result of said operation with a one-way function h to generate $h(k(+)b(+)R_m^{(k)})$, where b is a
10 predetermined value which indicates that said select information $b_m^{(k)}$ has selected the aimed value corresponding to said index k ; and

said control means makes a check for matching between said $h(k(+)b(+)R_m^{(k)})$ and said $h(k(+)b_m^{(k)}(+)R_m^{(k)})$ on said bulletin board.

93. The system of claim 86, wherein said aimed value transformer of
15 said each participant device comprises:

a conversion table memory which has stored therein a conversion table which defines indexes $k = 1, 2, \dots, K$ corresponding to K kinds of values selectable as aimed values, for converting said aimed value PR_m to the corresponding index k_m ;

20 initial value updating means which, for each index k , processes an initial value with a one-way function h and adds the processed initial value with select information $b_m^{(k)}$ for said index k to obtain an updated initial value and repeats this processing until $k = K$ is reached, thereby generating $H_m^{(K)}$;

a one-way function h processor for outputting said updated initial
25 value $H_m^{(k)}$ from said initial value updating means as said aimed value information;

select information generator which generates said select information

$b_m^{(k)}$ whether said aimed value corresponds to each index k from at least k_m to K ;

a concatenator which concatenates said $H_m^{(k-1)}$ from said one-way function h processor and said select information $b_m^{(k)}$ to generate $H_m^k = h(H_m^{(k-1)} || b_m^{(k)})$;

5 $1) || b_m^{(k)}$;

a buffer which temporarily holds the output from said concatenator and outputs said output for the next value of said index k ;

a storage part which, for each value of said index k , stores $H_m^{(k)}$ corresponding thereto; and

10 a second one-way function h processor by which $H_m^{(k)}$, obtained by repeating processing until $k = K$, is processed with a one-way function h to generate $h(H_m^{(k)})$, said $h(H_m^{(k)})$ being output as said aimed value information;

wherein said sending means is a means which responds to a request of said server device for said index k to read out $H_m^{(k)}$ from said storage part and

15 send said $H_m^{(k)}$ to said server device;

in said server device:

there are published on said bulletin board, as said aimed value information, $h(H_m^{(k)})$ obtained by processing, with a one-way function h , $H_m^{(k)}$ generated by said each participant device which, upon each processing of said
20 initial value with a one-way function h , added the processed value with select information $b_m^{(k)}$ indicating whether said value was an aimed value for each value of said index k and repeated this processing from at least the index k_m corresponding to said aimed value to the upper limit value K of said index k ;

said initial value updating means includes a one-way function h
25 processor by which $\{H_m^{(k-1)}, b_m\}$ received from said each participant device in answer to an inquiry for said index k is processed with a one-way function h to generate $H_m^{(k)} = h(H_m^{(k-1)} || b_m^{(k)})$; and

said server device includes an updated initial value comparator for making a check to see if said $H_m^{(k)}$ matches $H_m^{(k)}$ in $\{H_m^{(k)}, b_m^{(k+1)}\}$ previously received.

94. The system of claim 86, wherein said aimed value transformer of
5 said each participant device comprises:

a conversion table memory which has stored therein a conversion table which defines indexes $k = 1, 2, \dots, K$ corresponding to K kinds of values selectable as aimed values, for converting said aimed value PR_m to the corresponding index k_m ;

10 a one-way function g processor which processes said initial value IV_m with a one-way function g by a predetermined number of times x_m to generate $g^{x_m}(IV_m)$;

a one-way function h processor which processes said $g^{x_m}(IV_m)$ with a one-way function h $K-k_m$ times to generate $H_m^{(K)} = h^{K-k_m}(g^{x_m}(IV_m))$ as said
15 aimed value information; and

response generating means which responds to a request from said server device for k to decide whether $k=k_m$, and if true, generates $H_m^{(k-1)} = h^{k-k_m-1}(g^{x_m}(IV_m))$, and if false, generates $H_m^{(k-1)} = g^{x_m-1}(IV_m)$; and

wherein said sending means sends said $H_m^{(k-1)}$ in response to said
20 request from said server device for said k ; and

in said server device:

there is published on said bulletin board $H_m^{(K)} = h^{K-k_m}(g^{x_m}(IV_m))$ as said aimed value information received from said each participant device, which further comprises a one-way function h processor by which $H_m^{(k-1)}$ received
25 from said each participant device as an answer to an inquiry for said k is processed with a one-way function h to generate $h(H_m^{(k-1)})$, and a one-way function g processor for processing said answer $H_m^{(k-1)}$ with a one-way

function g to generate $g(H_m^{(k-1)})$; and

said control means: makes a check to see if said $h(H_m^{(k-1)})$ matches said aimed value information $H_m^{(K)}$ published on said bulletin board; if a match is detected, updates said aimed value information $H_m^{(K)}$ with said $H_m^{(k-1)}$ and decrements said index k on said counter by one; and if a mismatch is detected, makes a check to see if said $g(H_m^{(k-1)})$ matches said aimed value information $H_m^{(K)}$; and if a match is detected, determines, based on k and m at that time, the maximum or minimum aimed value PR_m and the participant device m having offered said value PR_m .

95. The system of claim 86, 87, 88, 91, 92, 93 or 94, wherein said aimed value transformer of said each participant device comprises;

a conversion table memory which has stored therein a conversion table which defines the relationships between a sequence of values selectable as said aimed values and a sequence of indexes k of integral values respectively corresponding thereto, for converting said aimed value PR_m to the corresponding index k_m ;

a fraction calculating part which, letting an arbitrary aimed value PR be represented by $PR = F(k) + Q$, where $F(k)$ is a value in said conversion table corresponding to said k and Q is a fraction which is a positive integer which satisfies $F(k+1) - F(k) > Q \geq 0$, calculates said fraction $Q_m = PR_m - F(k_m)$ based on $F(k_m)$ obtained from said conversion table and said aimed value PR_m ; and

a one-way function h processor which processes said initial value IV_m with said one-way function h by the number of times corresponding to said k_m to generate said aimed value information; and

wherein said sending means sends said fraction Q_m to said server device together with said aimed value information; and

in said server device:

there is published on said bulletin board said fraction Q_m received from said each participant device together with said aimed value information; and said server device comprises:

- 5 a sequencer for deciding the sequence of said fractions Q_m on said bulletin board; and
- select information comparator for checking whether said select information $b_m^{(k)}$ is equal to a value b indicating the selection of the aimed value corresponding to said index k in said decided sequence of fractions Q_m .
- 10 96. The system of claims 86, 87, 88, 91, 92, 93 or 94, wherein said sequence of index values k and said sequence of values selectable as said aimed values on said conversion table are monotone increasing values in the same direction, and said server device determines the maximum aimed value.
- 15 97. The system of claims 86, 87, 88, 91, 92, 93 or 94, wherein said sequence of index values k and said sequence of values selectable as said aimed values on said conversion table are monotone increasing values in opposite directions, and said server device determines the minimum aimed value.

ABSTRACT OF THE DISCLOSURE

A bid-opening device 20 receives from each bidding device 10_m a bidding price index $\gamma_m = g(h^k(IV_m))$ (where IV_m is an initial value, h^k indicates k-times processing with a one-way function h and g is a one-way function) and its identifier ID_m . The received information is stored on a common bulletin board 25. $D_m = h^k(IV_m)$ (where $D_m = g(D_m)$ is generated with k set as the upper limit value K of the bidding price. The bulletin board 25 is checked for γ_m which matches this D_m . If no match is found, m is incremented by one, and the check for γ_m - D_m matching is made for each of m bidding devices. Upon completion of the matching for all the bidding devices, k is decremented by one, and a check is made for γ_m which matches $D_m = g(h^k(IV_m))$, and the index k for which they match is determined as the highest price bid. The bid-opening device 20 outputs that k and the identifier ID_m of γ_m .

FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5





FIG. 7







FIG. 8

FIG. 9






FIG. 10

FIG. 11





FIG. 12







FIG. 13

FIG. 14







FIG. 15

FIG. 16






FIG. 17

FIG. 18





FIG. 19






FIG. 20

FIG. 21




FIG. 23





FIG. 24







FIG. 25

FIG. 26






FIG. 27

FIG. 28





FIG. 29






FIG. 30





FIG. 31

FIG. 32







FIG. 33

FIG. 34



DECLARATION FOR PATENT APPLICATION

As a below-named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name.

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled:

the specification of which: (check one)

[XX] is attached hereto. [] was filed on 19, as United States Patent Application Serial No. or PCT International Application Number, and was amended on 19 (if applicable).

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to the patentability of this application in accordance with 37 CFR § 1.56(a).

Prior Foreign Application(s): I hereby claim foreign priority benefits under 35 U.S.C. § 119(a)-(d) or § 365(b) of any foreign application(s) for patent or inventor's certificate listed below, or § 365(a) of any PCT international application which designated at least one country other than the United States of America, listed below and have also identified below any foreign application for patent or inventor's certificate having a filing date before that of the application on which priority is claimed:

205004/99

Japan

19/07/99

Priority Claimed

[X] []

(Application No.)

(Country)

(Day/Month/Year Filed)

Yes No

247060/99

Japan

01/09/99

[X] []

(Application No.)

(Country)

(Day/Month/Year Filed)

Yes No

2000-16020

Japan

25/01/00

[X] []

(Application No.)

(Country)

(Day/Month/Year Filed)

Yes No

2000-47323

Japan

24/02/00

[X] []

(Application No.)

(Country)

(Day/Month/Year Filed)

Yes No

I hereby claim the benefit under Title 35, United States Code § 119(e) of any United States provisional application(s) listed below:

Application No.

Filing Date

I hereby claim the benefit under 35 U.S.C. § 120 of any United States application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by 35 U.S.C. § 112, first paragraph, I acknowledge the duty to disclose material information as defined in 37 CFR § 1.56(a) which occurred between the filing date of the prior application and the national or PCT international filing date of this application:

(U.S. Application Serial No.)

(U.S. Filing Date)

(Status--patented, pending, abandoned)

(U.S. Application Serial No.)

(U.S. Filing Date)

(Status--patented, pending, abandoned)

I hereby appoint Elliott I. Pollock, Registration No. 16,906; George Vande Sande, Registration No. 17,276; Burton A. Amernick, Registration No. 24,852; Stanley B. Green, Registration No. 24,351; Richard Wiener, Registration No. 18,741; Townsend M. Belser, Jr., Registration No. 22,956; Morris Liss, Registration No. 24,510; Martin Abramson, Registration No. 25,787; George R. Pettit, Registration No. 27,369; Elzbieta Chlopek, Registration No. 32,767; Eric J. Franklin, Registration No. 37,134; and Jeffri A. Kaminski, Reg. No. 42,709, my attorneys with full power of substitution and revocation, to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith.

Send Correspondence and Direct Telephone Calls to:

[name]

(202) 331-7111

[name]

Pollock, Vande Sande & Amernick, R.L.L.P.

P.O. Box 19088

Washington, D.C. 20036-3425 U.S.A.

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true, and further that these statements are made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under 18 U.S.C. § 1001 and that such willful false statements may jeopardize the validity of the application or any patent issued thereon

Full name of sole or first inventor: KUNIO KOBAYASHI

Inventor's Signature: *Kunio Kobayashi* Date: July 7, 2000

Residence Address: B-203, 4-22-14, Kamariyashigashi, Kanazawa-ku, Yokohama-shi, Kanagawa 236-0042

Citizenship: Japan Japan

Post Office Address: C/O NIPPON TELEGRAPH AND TELEPHONE CORPORATION, 20-2 Nishi-Shinjuku 3-chome, Shinjuku-ku, Tokyo 163-1419, Japan

See next page for additional inventors

12702905

DECLARATION FOR PATENT APPLICATION

Page Two

Full name of second joint inventor (if any): HIKARU MORITAInventor's Signature *Hikaru Morita* Date July 7, 2000Residence Address 1-64-3, Tomiokanishi, Kanazawa-ku, Yokohama-shi, Kanagawa 236-0052 JapanCitizenship JapanPost Office Address C/O NIPPON TELEGRAPH AND TELEPHONE CORPORATION, 20-2 Nishi-Shinjuku 3-chome,
Shinjuku-ku, Tokyo 163-1419, JapanFull name of third joint inventor (if any): KOUTAROU SUZUKIInventor's Signature *Koutarou Suzuki* Date July 7, 2000Residence Address 2-1-3-2-303, Hayashi, Yokosuka-shi, Kanagawa 238-0315 JapanCitizenship JapanPost Office Address C/O NIPPON TELEGRAPH AND TELEPHONE CORPORATION, 20-2 Nishi-Shinjuku 3-chome,
Shinjuku-ku, Tokyo 163-1419, Japan

Full name of fourth joint inventor (if any): _____

Inventor's Signature _____ Date _____

Residence Address _____

Citizenship _____

Post Office Address _____

Full name of fifth joint inventor (if any): _____

Inventor's Signature _____ Date _____

Residence Address _____

Citizenship _____

Post Office Address _____

Full name of sixth joint inventor (if any): _____

Inventor's Signature _____ Date _____

Residence Address _____

Citizenship _____

Post Office Address _____

Full name of seventh joint inventor (if any): _____

Inventor's Signature _____ Date _____

Residence Address _____

Citizenship _____

Post Office Address _____

Full name of eighth joint inventor (if any): _____

Inventor's Signature _____ Date _____

Residence Address _____

Citizenship _____

Post Office Address _____